

# Rittal – The System.

Faster – better – everywhere.

## Enclosure Light – SZ 9968.109

Date : May 29, 2018

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



# Enclosure Light – SZ 9968.109

created: 29.05.2018 build on [www.rittal.com/us-en](http://www.rittal.com/us-en)



## Product description

**Benefits:** Designed for quick and easy installation  
External terminal block allows no need to disassemble the light to make electrical connections  
Available in 15 or 18 watt rating, they can be used with or without the Rittal door switch.  
Equipped with interference suppression capacitor or a RFI filter, they also come with or without a lamp shade or 115 V U.S. style receptable.

**Material:** Lamp holder: polycarbonate  
Switch: polyester and polycarbonate  
Terminal block: nylon

**Color:** RAL 7044

**Supply includes:** Fasteners

## Product features

**Dimensions:** Height: 110 mm (4.3 ")  
Width: 620 mm (24 ")  
Depth: 45 mm (1.8 ")

**Rated operating voltage:** 120 V, 60 Hz

**Equipment (electrical):** Light (bulb): Cool white fluorescent  
Switch (type): On/off rocker switch

**Luminous flux:** 718 lm

**Connection options:** L1, N, GND

<b>Light – installation type:</b>	Screw fastening
<b>Light – mounting option:</b>	TS vertical profile, direct TS roof frame (horizontal profile), direct
<b>Packaging unit:</b>	1 pc(s).
<b>Weight/packaging unit:</b>	2.3 kg (5.1 lb.)
<b>EAN:</b>	19129