## Rittal - The System.

Faster – better – everywhere.

## Wallmounted enclosure − WM 8017.588

Date: May 25, 2018



ENCLOSURES POWER DISTRIBUTION CLIMATE CONTROL IT INFRASTRUCTURE SOFTWARE & SERVICES

## Wallmounted enclosure - WM 8017.588 - WM483612NC

created: 25.05.2018 build on www.rittal.com/us-en



<b>Prod</b>	uct	daed	rin	tion
riou	uci	uesi	oi ip	เเบา

Material: Door: Carbon steel, all-round foamed-in PU seal

Housing: Carbon steel

**Surface finish:** Housing and door: Dipcoat primed, powder-coated on the outside, textured paint

Mounting plate: Zinc-plated

Color: RAL 7035

Protection category IP to IEC 60 529:

IP 66

Protection category

NEMA:

NEMA 4

**Supply includes:** Housing with door(s)

Left hand hinge Mounting plate

Rear wall mounting holes 3-point latching L-Handle

## **Product features**

**Dimensions:** Height: 1200 mm (47 ")

Width: 900 mm (35 ") Depth: 300 mm (12 ")

Material thickness:: Housing: 2 mm (0.08 ")

Door: 2 mm (0.08 ")

Mounting plate: 2.5 mm (0.1 ")

Mounting plate: Height: 1155 mm (45 ")

Width: 840 mm (33 ")

© Rittal 2018

3-point locking system:	yes
Packaging unit:	1 pc(s).
Weight/packaging unit:	82 kg (180.8 lb.)
EAN:	83165
Approvals	
Approvals:	UL

© Rittal 2018 2