

S9736

14T8/LED/48-840/DR 14 watt T8 LED; Medium bi-pin base; 4000K; 50000 average rated hours; 1800 lumens

Features

- Direct Replacement for use on Instant Start and Rapid Start ballasts with no rewiring required*
- Solid State LED lighting
- High efficacy
- Long lifeDLC Qualified
- 5 year Limited warranty
- Dimmable*
- Compatible with emergency ballasts*
- All glass tube

*May not be compatible with all rapid start, dimmable, and emergency ballasts.

Available March 2016

View: Ballast Compatibility Chart



S9736

Item Number	r	UPC	Voltag	je Wat	ts Fluore	scent Equivalent	Lamp Shape	Base	ANSI Base
S9736	0-	45923097362	120-27	77 14		25W-32W	Т8	Medium BiPin	G13
Lamp Co	ode	Dimmable/N Dimmabl		Finish	MOL In Inches	MOD In Inches	Initial Lumens	Average Rated Hours	Kelvin Temp
14T8/LED/48-840/D		R Non-Dimmable		White	48"	1.00"	1800	50000	4000
Color	CRI	Beam Spread	Pack F	Package T	ype RoH	S Compliant	UL or ETL	UL Classifi	cation

Color	CRI	Beam Spread Deg	Pack	Package Type	RoHS Compliant	UL or ETL Listed	UL Classification			
Cool White	82	230	10 Box		Yes	Yes	cETLus - Damp Location Rated			
Warranty										



National Toll-Free: 800.43.SATCO (800.437.2826) www.satco.com

Distribution Centers: New York, Florida, Texas, Washington, California, Puerto Rico Corporate Offices: 110 Heartland Blvd., Brentwood, NY 11717 800.437.2826 631.243.2022 Fax 631.243.2027



@2012, Satco Products, Inc. Not responsible for typographical errors. 06/12 S1051