
#### DIMMING HALOGEN LAMPS GREATLY REDUCES LAMP LIFE

WARNING: Use of other manufacturer's components will void warranty, safety listing and create a potential safety hazard.



**NOTE**: LOOSEN SCREWS TO ROTATE SHADE IF

**C**. Making sure contacts on head are aligned with cable, press head onto the track until both sides of head snap onto the track.

B. Snap (12V,20W-MRC11) lamp into socket.

A. Space Accent lights no closer than 6" apart.

(NOSE ONLY WITH AMBIANCE 105° CABLE)
ACCENT LIGHT INSTALLATION

### INSTALLATION AND SAFETY INSTRUCTIONS

## **FOR YOUR SAFETY**

HC-205

**WARNING**: Be sure the electricity to the system you are working on is turned off; either the fuse removed or the circuit breaker set at off

WARNING: RISK OF SHOCK, 24V SYSTEM NOT SUITABLE FOR OUTDOOR USE.

**CAUTION**: RISK OF FIRE. USE ONLY 12V LAMPS WITH 12V SYSTEMS. USE OF 12V LAMPS WITH 24V SYSTEM MAY RESULT IN DAMAGE TO SYSTEM AND SURROUNDING AREA.

# (USE ONLY WITH AMBIANCE 105° CABLE) CAUTION-RISK OF FIRE MAX 20 WATT TYPE GU4 Bi-Pin MRC11

ATTENTION RISQUE D'INCENDIE: UTILISATION SEULEMENT AVEC LAMPES 12V 12V SYSTEMS. UTILISATION DE LAMPES 12V 24V AVEC SYSTEME PEUT PROVOQUER DES DOMMAGES AU SYSTÈME ET ALENTOURS.

# (UTILISER UNIQUEMENT AVEC LE CÂBLE 105° DE L'AMBIANCE)


# ATTENTION-RISQUE D'INCENDIE MAX 20 WATT TYPE GU4 Bi-Pin MRC11

## IMPORTANT SAFETY INSTRUCTIONS

- **1.** Bulb gets hot quickly! Turn off and allow to cool to replace bulb.
- **2. Do not** remain in light if skin feels warm.
- 3. Do not look directly at lighted bulb.
- 4. Minimum distance from combustible materials. To front of lamp is 4", from lamp rim is 3/4" (see dia gram). Allow clearance not only for shelf but also for items that might be displayed on the shelf.
  061714

#### DIMMING HALOGEN LAMPS GREATLY REDUCES LAMP LIFE

WARNING: Use of other manufacturer's components will void warranty, safety listing and create a potential safety hazard.



NECESSARY.

NOTE: LOOSEN SCREWS TO ROTATE SHADE IF

C. Making sure contacts on head are aligned with cable, press head onto the track until both sides of head snap onto the track.

B. Snap (12V,20W-MRC11) lamp into socket.

A. Space Accent lights no closer than 6" apart.

(NOSE ONLY WITH AMBIANCE 105° CABLE)
ACCENT LIGHT INSTALLATION

## INSTALLATION AND SAFETY INSTRUCTIONS

## **FOR YOUR SAFETY**

HC-205

**WARNING**: Be sure the electricity to the system you are working on is turned off; either the fuse removed or the circuit breaker set at off

WARNING: RISK OF SHOCK, 24V SYSTEM NOT SUITABLE FOR OUTDOOR USE.

**CAUTION**: RISK OF FIRE. USE ONLY 12V LAMPS WITH 12V SYSTEMS. USE OF 12V LAMPS WITH 24V SYSTEM MAY RESULT IN DAMAGE TO SYSTEM AND SURROUNDING AREA.

# (USE ONLY WITH AMBIANCE 105° CABLE) CAUTION-RISK OF FIRE MAX 20 WATT TYPE GU4 Bi-Pin MRC11

ATTENTION RISQUE D'INCENDIE: UTILISATION SEULEMENT AVEC LAMPES 12V 12V SYSTEMS. UTILISATION DE LAMPES 12V 24V AVEC SYSTEME PEUT PROVOQUER DES DOMMAGES AU SYSTÈME ET ALENTOURS.

# (UTILISER UNIQUEMENT AVEC LE CÂBLE 105° DE L'AMBIANCE)

# ATTENTION-RISQUE D'INCENDIE MAX 20 WATT TYPE GU4 Bi-Pin MRC11

### IMPORTANT SAFETY INSTRUCTIONS

- **1.** Bulb gets hot quickly! Turn off and allow to cool to replace bulb.
- **2. Do not** remain in light if skin feels warm.
- 3. Do not look directly at lighted bulb.
- 4. Minimum distance from combustible materials. To front of lamp is 4", from lamp rim is 3/4" (see dia gram). Allow clearance not only for shelf but also for items that might be displayed on the shelf. 061714