Product data sheet Characteristics

13959

mini Kaedra - for modular device - 1 openings - 8 modules - 1 terminal block

Product availability: Stock - Normally stocked in distribution facility

Price*: 200.00 USD



Main

Kaedra	
Weatherproof enclosure	
Mini enclosure for modular device	
1 terminal block 8 holes 1 marking kit 1 terminal block support	

Complementary

		isclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications
Main		ts for s
Range	Kaedra	
Product or component type	Weatherproof enclosure	ese
Enclosure type	Mini enclosure for modular device	
Accessories included with enclosure	1 terminal block 8 holes 1 marking kit 1 terminal block support	y or reliabilit
Complementary		ning suitabili
Enclosure mounting	Surface	termi
Number of 18 mm modules per row	8	or de
Total number of 18 mm modules	8	sed f
Number of horizontal rows	1	p pe n
Electrical insulation class	Class II Double insulation	is not to
Provided equipment	1 marking kit 1 terminal block 8 holes 1 terminal block support	titute for and
Type of front cover	Transparent	sqns
Power dissipation in W	15 W	as a
[In] rated current	63 A	
Type of rail	DIN	ot inte
Number of pre-cutouts PG ISO	5	
Number of terminal blocks	1 with 8 outgoers	ntation
Distribution block outgoers	4 x 10 mm ² 4 x 16 mm ²	noop
Locking options description	Optional keylock	This
Enclosure material	Self-extinguishing polymer	
Width	7.68 in (195 mm)	- Disclai

Height	7.87 in (200 mm)	
Depth	4.41 in (112 mm)	
Colour	Door : transparent green Enclosure : light grey (RAL 7035)	

Environment

Standards	IEC 60529 EN 50102 IEC 60439-3 EN 50262 IEC 670	
Fire resistance	1382 °F (750 °C) conforming to IEC 60695-2-1	
IP degree of protection	IP65 conforming to IEC 60529	
IK degree of protection	IK09 conforming to EN 50102	
Environmental characteristic	UV resistant class 3 conforming to ISO 4582 2010 Ultraviolet degradation test conforming to ISO 4892-2 2013	
Overvoltage category	II	
Ambient air temperature for operation	-13140 °F (-2560 °C)	

Ordering and shipping details

ordering and emponing details		
Category	00908 - C60N SUPPLEMENTARY PROTECTORS	
Discount Schedule	DE2	
GTIN	00785901700791	
Nbr. of units in pkg.	1	
Package weight(Lbs)	1.890000000000001	
Returnability	N	
Country of origin	IT	

Contractual warranty

Warranty period	18 months	
vvarranty period	18 months	