

Product data sheet

Characteristics

15T2F

TRANSFORMER DRY 3PH 15KVA

480V-208Y/120V

Product availability : Stock - Normally stocked in distribution facility



Price* : 4644.00 USD



Main

Product or component type	Dry Sealed Transformer
Primary voltage	480 V delta
Secondary voltage	208Y/120 V
Number of tap-offs	2 5 % FCBN

Complementary

Box number	14C
Phase	3 phases
Primary voltage	480 V delta : 208Y/120 V
Rated power in VA	15 kVA
Temperature rise	115 °C
Height	14.75 in
Width	19.1 in
Depth	12.25 in
Enclosure mounting	Wall mounted
Enclosure material	Painted sheet steel

Environment

NEMA degree of protection	NEMA 3R
Insulation temperature	356 °F (180 °C)
Product certifications	CSA cULus UL listed

Ordering and shipping details

Category	16277 - RESIN LVGP XFMR
----------	-------------------------

Discount Schedule	PE2
GTIN	00785901359500
Nbr. of units in pkg.	1
Package weight(Lbs)	323
Returnability	Y
Country of origin	MX

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1430 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold
Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations

Contractual warranty

Warranty period	18 months
-----------------	-----------