

# Product data sheet

## Characteristics

# 6T2F

## TRANSFORMER DRY 3PH 6KVA

### 480V-208Y/120V

Product availability : Stock - Normally stocked in distribution facility



Price\* : 2310.00 USD



### Main

Product or component type	Dry Sealed Transformer
Primary voltage	480 V delta
Secondary voltage	208Y/120 V
Number of tap-offs	2 5 % FCBN

### Complementary

Box number	12C
Phase	3 phases
Primary voltage	480 V delta : 208Y/120 V
Rated power in VA	6 kVA
Temperature rise	115 °C
Height	13.5 in
Width	14.75 in
Depth	9 in
Enclosure mounting	Wall mounted
Enclosure material	Painted sheet steel

### Environment

NEMA degree of protection	NEMA 3R
Insulation temperature	356 °F (180 °C)
Product certifications	CSA UL listed cULus

### Ordering and shipping details

Category	16277 - RESIN LVGP XFMR
----------	-------------------------

Discount Schedule	PE2
GTIN	00785901359470
Nbr. of units in pkg.	1
Package weight(Lbs)	165
Returnability	Y
Country of origin	MX

### Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1430 - Schneider Electric declaration of conformity <a href="#">Schneider Electric declaration of conformity</a>
REACH	Reference not containing SVHC above the threshold <a href="#">Reference not containing SVHC above the threshold</a>
Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations

### Contractual warranty

Warranty period	18 months
-----------------	-----------