

Product availability : Stock - Normally stocked in distribution facility

Price* : 6143.00 USD



Main

Range	PratiKa
Product or component type	Interlocked socket
Device short name	PratiKa socket
Plug, socket category	Low voltage
Poles description	3P + E
Network type	AC
Outlet standard	Industrial

Complementary

Line Rated Current	125 A
[Ue] rated operational voltage	380...415 V
Network frequency	50/60 Hz
Protection type	Residual current breaker with overcurrent protection (RCBO)
Plug, socket material	Housing: self-extinguishing engineering polymer
Connections - terminals	Captive screws
Cable cross section	<= 0.15 in ² (95 mm ²)
Cable entry	Cable gland
Thread type	Pg 42
Product weight	24.47 lb(US) (11.1 kg)
Height	27.95 in (710 mm)
Width	10.63 in (270 mm)
Depth	8.46 in (215 mm)
Colour	Grey (RAL 7035)
Voltage colour	Red

Environment

Standards	EN 60309-1
-----------	------------

EN 60309-2

IP degree of protection	IP65 conforming to IEC 60529
IK degree of protection	IK08 conforming to EN 62262
Fire resistance	1760 °F (960 °C) conforming to IEC 60695-2-11
Relative humidity	50 % (104 °F (40 °C)) 70 % (86 °F (30 °C)) 90 % (68 °F (20 °C))
Ambient air temperature for operation	95 °F (35 °C) (86400 s)

Ordering and shipping details

Category	00033 - DT SWITCH,NEMA1
Discount Schedule	DE1
GTIN	00785901430018
Nbr. of units in pkg.	1
Package weight(Lbs)	95
Returnability	Y
Country of origin	US

Contractual warranty

Warranty period	18 months
-----------------	-----------