

Product availability : Stock - Normally stocked in distribution facility



Price* : 2298.00 USD



Main

Product or component type	Combination Starter
Range of product	S
Control circuit	Control circuit transformer
Provided equipment	2 fuses primary circuit 1 fuse secondary circuit
Control type	Selector switch HAND-OFF-AUTO
NEMA degree of protection	NEMA 1 painted sheet steel with external reset
Auxiliary contact composition	Without
Motor power hp	5 hp 460 V AC 3 phases 5 hp 575 V AC 3 phases
Poles description	3P
System Voltage	600 V AC
NEMA size	0
[Uc] control circuit voltage	120 V AC 60 Hz secondary circuit 480 V AC 60 Hz primary circuit
Local signalling	No indicator
Motor starter type	Non reversing
Thermal overload type	Melting alloy
Number of thermal units required	3
Disconnecter device type	Fusible disconnect switch R 30 A

Ordering and shipping details

Category	21212 - 8538,39SB(NOT S*R,S*T,S*W)
Discount Schedule	CP1
GTIN	00785901020806
Nbr. of units in pkg.	1
Package weight(Lbs)	35.52000000000003
Returnability	N

Country of origin	MX
-------------------	----

Offer Sustainability

Sustainable offer status	Not Green Premium product
RoHS (date code: YYWW)	Will be compliant on 3Q2014 Will be compliant on 3Q2014
REACH	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold

Contractual warranty

Warranty period	18 months
-----------------	-----------
