Product data sheet Characteristics

8910DPA33V02U1 CONTACTOR 600VAC 30AMP DPA +OPTIONS

Product availability: Stock - Normally stocked in distribution facility



Price*: 75.00 USD



Main

Product or component type	Definite Purpose Contactor	
Line Rated Current	30 A	
Poles description	3P	
Pole contact composition	3 NO	
Range of product	DPA	±

Complementary

Motor power hp	2 hp 115 V AC 1 phase	,
meter pewer rip	5 hp 230 V AC 1 phase	ğ
	· · · · · · · · · · · · · · · · · · ·	<u>.</u> .
	10 hp 230 V AC 3 phases	§
	15 hp 460 V AC 3 phases	9
	20 hp 575 V AC 3 phases	, and the second se
Locked rotor rated current	150 A 460 V AC	-
	120 A 575 V AC	=
	180 A 277 V AC	£
System Voltage	600 V AC	
[Uc] control circuit voltage	110 V AC 50 Hz	
-	120 V AC 60 Hz	j.
Phase	3 phases	
Electrical connection	Binder head	<u>y</u> 0

Environment

Product certifications	CE	
	CSA UL listed	
	OL listed	

Ordering and shipping details

Category	21343 - 8910 DPA 3_(30 AMP)	er: ⊒_
Discount Schedule	CP1B	claim

GTIN	00785901112426
Nbr. of units in pkg.	1
Package weight(Lbs)	1.04
Returnability	Y
Country of origin	CN

Offer Sustainability

Sustainable offer status	Not Green Premium product
RoHS (date code: YYWW)	Will not be compliant
	Will not be compliant
REACh	Reference not containing SVHC above the threshold
	Reference not containing SVHC above the threshold

Contractual warranty

Warranty period	18 months