

Product availability : Stock - Normally stocked in distribution facility



Price\* : 354.00 USD



### Main

Product or component type	Definite Purpose Starter
Line Rated Current	25 A
Motor power hp	5 hp 230 V AC 1 phase 2 hp 115 V AC 1 phase
System Voltage	600 V AC
[Uc] control circuit voltage	120 V AC 60 Hz 110 V AC 50 Hz
Phase	1 phase

### Complementary

Enclosure material	Painted sheet steel
NEMA degree of protection	NEMA 1
Locked rotor rated current	125 A 460 V AC 100 A 575 V AC 150 A 230 V AC
Poles description	2P
Range of product	DPS
Thermal overload type	Melting alloy
Number of thermal units required	1

### Ordering and shipping details

Category	21381 - 8911 DP
Discount Schedule	CP1
GTIN	00785901024651
Nbr. of units in pkg.	1
Package weight(Lbs)	5.620000000000001
Returnability	Y
Country of origin	CN

Offer Sustainability

Sustainable offer status	Not Green Premium product
RoHS (date code: YYWW)	Will not be compliant Will not be compliant
REACH	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold

Contractual warranty

Warranty period	18 months
-----------------	-----------