

Product availability : Stock - Normally stocked in distribution facility



Price* : 459.00 USD



Main

Product or component type	Definite Purpose Starter
Line Rated Current	40 A
Motor power hp	3 hp 115 V AC 1 phase 7.5 hp 230 V AC 1 phase 10 hp 230 V AC 3 phases 25 hp 575 V AC 3 phases 20 hp 460 V AC 3 phases
System Voltage	600 V AC
[Uc] control circuit voltage	208...240 V AC 60 Hz 220 V AC 50 Hz
Phase	3 phases

Complementary

Enclosure material	Painted sheet steel
NEMA degree of protection	NEMA 1
Locked rotor rated current	160 A 575 V AC 240 A 230 V AC 200 A 460 V AC
Poles description	3P
Range of product	DPS
Thermal overload type	Melting alloy
Number of thermal units required	3

Ordering and shipping details

Category	21381 - 8911 DP
Discount Schedule	CP1
GTIN	00785901024712
Nbr. of units in pkg.	1
Package weight(Lbs)	5.6500000000000004

Returnability	Y
Country of origin	CN

Offer Sustainability

Sustainable offer status	Not Green Premium product
RoHS (date code: YYWW)	Will not be compliant Will not be compliant
REACH	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold

Contractual warranty

Warranty period	18 months
-----------------	-----------