

Product availability : Stock - Normally stocked in distribution facility



Price\* : 638.00 USD



### Main

Product	Definite Purpose Starter
Line Rated Current	50 A
Horsepower Rating	3 hp 115 V AC 1 phase 10 hp 230 V AC 1 phase 30 hp 575 V AC 3 phases 15 hp 230 V AC 3 phases 30 hp 460 V AC 3 phases
System Voltage	600 V AC
Control Circuit Voltage	220 V AC 50 Hz 208...240 V AC 60 Hz
Phase	3 phases

### Complementary

Enclosure Rating	Not rated (open device)
Locked Rotor Amperes	200 A 575 V AC 300 A 230 V AC 250 A 460 V AC
Number of Poles	3P
Range	DPS
Overload Type	Melting alloy
Number of Thermal Units	3

### Ordering and shipping details

Category	21381 - 8911 DP
Discount Schedule	CP1
GTIN	00785901025207
Nbr. of units in pkg.	1
Package weight(Lbs)	2.9399999999999999
Returnability	Y

---

Country of origin	CN
-------------------	----

---

### Offer Sustainability

---

Sustainable offer status	Not Green Premium product
RoHS (date code: YYWW)	Will not be compliant Will not be compliant
REACH	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold

---

### Contractual warranty

---

Warranty period	18 months
-----------------	-----------

---