

Product data sheet

Characteristics

8940SSF4100L9

PUMP PANEL 480VAC 135AMP NEMA +OPTIONS

Product availability : Stock - Normally stocked in distribution facility



Price* : 7718.00 USD



Main

| | |
|-------------------|---------------------------------------|
| Device short name | SS |
| Enclosure type | Enclosure weatherproof indoor/outdoor |
| Range of product | Well-Guard |

Complementary

| | |
|--------------------------|--|
| Associated fuse rating | 200 A |
| Control type | Push-button START Selector switch HAND-OFF-AUTO |
| Depth | 10.37 in |
| Device mounting | Surface |
| Electrical connection | Screw terminal |
| Height | 49 in |
| Motor power hp | 100 hp 460 V AC 3 phases |
| Network number of phases | 3 phases |
| Number of poles | 3 |
| Permissible voltage | <= 480 V AC |
| Protection type | Switch-disconnector fuse |
| Stage of operation | Common control circuit |
| Thermal overload type | Solid state Motor Logic class 10 |
| Width | 19.15 in |

Environment

| | |
|---------------------------|-------------------|
| NEMA degree of protection | NEMA 3R |
| Product certifications | NEMA UL listed |

Ordering and shipping details

| | |
|-----------------------|----------------------|
| Category | 21389 - 8940 NSE,NSF |
| Discount Schedule | CP1 |
| GTIN | 00785901765417 |
| Nbr. of units in pkg. | 1 |
| Package weight(Lbs) | 147 |
| Returnability | Y |
| Country of origin | MX |

Offer Sustainability

| | |
|--------------------------|--|
| Sustainable offer status | Not Green Premium product |
| RoHS (date code: YYWW) | Will not be compliant Will not be compliant |
| REACH | Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold |

Contractual warranty

| | |
|-----------------|-----------|
| Warranty period | 18 months |
|-----------------|-----------|