

9001BW159

CONTROL STATION 600VAC 5A T-B Ø30

Standard Duty Momentary Pushbuttons 1NO-1NC

Product availability : Stock - Normally stocked in distribution facility



Price* : 269.00 USD



Main

Range of product	Harmony 9001BW
Product or component type	Complete control station
Device short name	9001BW
Control station application	Two functions
Colour of base of enclosure	Grey

Complementary

Material	Cast aluminium
Cable entry	1 entry for 1/2" - 14 NPT
CAD overall width	2.76 in (70 mm)
CAD overall height	4.25 in (108 mm)
CAD overall depth	3.58 in (91 mm)
Type of operator	Momentary
Control station composition	1 flush pushbutton, cap/operator or lens colour:black (without marking marking)
Contacts type and composition	1 C/O + 1 C/O
Mechanical durability	5000000 cycles
Connections - terminals	Screw-clamp terminal
[Ie] rated operational current	0.6 A at 600 V - utilisation category AC-1/DC-1 0.75 A at 480 V - utilisation category AC 1.5 A at 240 V - utilisation category AC 3.75 A at 120 V - utilisation category AC
Device mounting	Surface
Type of installation	Indoor/Outdoor

Environment

Ambient air temperature for storage	-40...158 °F (-40...70 °C)
-------------------------------------	----------------------------

Ambient air temperature for operation	-13...158 °F (-25...70 °C)
NEMA degree of protection	NEMA 1 NEMA 4
Standards	EN/IEC 60947-1 EN/IEC 60947-5-1 EN/IEC 60947-5-4 EN/IEC 60947-5-5 JIS C 4520 UL 508 CSA C22.2 No 14
Product certifications	CSA UL listed
Environmental characteristic	Waterproof Dustproof

Ordering and shipping details

Category	21421 - 9001 B (NOT BW70 - BW80)
Discount Schedule	CS1
GTIN	00785901177753
Nbr. of units in pkg.	1
Package weight(Lbs)	1.5
Returnability	N
Country of origin	MX

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 0921 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold
Product environmental profile	Available
Product end of life instructions	Available

Contractual warranty

Warranty period	18 months
-----------------	-----------