

# 9001BW242

## CONTROL STATION 600VAC 5A T-B Ø30

### Standard Duty Momentary Pushbuttons 2 N.O

Product availability : Stock - Normally stocked in distribution facility



Price\* : 270.00 USD



#### Main

Range of product	Harmony 9001BW
Product or component type	Complete control station
Device short name	9001BW
Control station application	Two functions
Colour of base of enclosure	Grey

#### Complementary

Material	Cast aluminium
Cable entry	1 entry for 1/2" - 14 NPT
CAD overall width	2.76 in (70 mm)
CAD overall height	4.25 in (108 mm)
CAD overall depth	3.58 in (91 mm)
Type of operator	Momentary
Control station composition	1 flush push-button, cap/operator or lens colour:black (FOR marking) white 1 flush push-button, cap/operator or lens colour:black (REV marking) white
Contacts type and composition	1 NO + 1 NO
Mechanical durability	5000000 cycles
Connections - terminals	Screw-clamp terminal
[Ie] rated operational current	0.6 A at 600 V - utilisation category AC-1/DC-1 0.75 A at 480 V - utilisation category AC 1.5 A at 240 V - utilisation category AC 3.75 A at 120 V - utilisation category AC
Device mounting	Surface
Type of installation	Indoor/Outdoor

#### Environment

Ambient air temperature for storage	-40...158 °F (-40...70 °C)
-------------------------------------	----------------------------

Ambient air temperature for operation	-13...158 °F (-25...70 °C)
NEMA degree of protection	NEMA 1 NEMA 4
Standards	EN/IEC 60947-1 EN/IEC 60947-5-1 EN/IEC 60947-5-4 EN/IEC 60947-5-5 JIS C 4520 UL 508 CSA C22.2 No 14
Product certifications	CSA UL listed
Environmental characteristic	Waterproof Dustproof

### Ordering and shipping details

Category	21421 - 9001 B (NOT BW70 - BW80)
Discount Schedule	CS1
GTIN	00785901856672
Nbr. of units in pkg.	1
Package weight(Lbs)	2.3799999999999999
Returnability	N
Country of origin	MX

### Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 0921 - Schneider Electric declaration of conformity <a href="#">Schneider Electric declaration of conformity</a>
REACH	Reference not containing SVHC above the threshold <a href="#">Reference not containing SVHC above the threshold</a>
Product environmental profile	Available
Product end of life instructions	Available

### Contractual warranty

Warranty period	18 months
-----------------	-----------