Product data sheet Characteristics

9001KYK31 **CONTROL STATION + OPERATORS**

Product availability: Stock - Normally stocked in distribution facility





Price*: 441.00 USD



Main

Range of product	Harmony 9001K
Product or component type	Complete control station
Device short name	KY
Provided equipment	Contact block Legend plate
Contact block name	KA1

Complementary

Enclosure/Cubicle description	Surface mounting	
Enclosure material	Die cast zinc alloy, colour : grey	
Type of installation	Indoor/Outdoor	
Control station composition	2 push-buttons with 3 NO + 3 NC contacts FORWARD-REVERSE-STOP	
Connections - terminals	Screw-clamp terminals	
[le] rated operational current AC	10 A	

Environment

NEMA degree of protection NEMA 3/4/13			NEMA degree of protection
---------------------------------------	--	--	---------------------------

Ordering and shipping details

Range of product Harmony 9001K Product or component type Complete control station Device short name KY Provided equipment Contact block Legend plate Contact block name KA1 Complementary Enclosure/Cubicle description Surface mounting Enclosure material Die cast zinc alloy, colour : grey Type of installation Indoor/Outdoor Control station composition 2 push-buttons with 3 NO + 3 NC contacts FORWARD-REVERSE-STOP Connections - terminals Screw-clamp terminals [le] rated operational current AC 10 A Environment NEMA 3/4/13 Ordering and shipping details Category 21426 - 9001 K (NOT KA,KM,KX) Discount Schedule CS1 GTIN 00785901513414 Nbr. of units in pkg. 1 Package weight(Lbs) 4.560000000000005 Returnability N			applications
Main Range of product Harmony 9001K Product or component type Complete control station Device short name KY Provided equipment Contact block Legend plate Contact block name KA1 Complementary Enclosure/Cubicle description Surface mounting Enclosure material Die cast zinc alloy, colour : grey Type of installation Indoor/Cutdoor Control station composition 2 push-buttons with 3 NO + 3 NC contacts FORWARD-REVERSE-STOP Connections - terminals Screw-clamp terminals [le] rated operational current AC Environment NEMA degree of protection NEMA 3/4/13 Ordering and shipping details Category 21426 - 9001 K (NOT KA,KM,KX) Discount Schedule CS1 GTIN 00785901513414 Nbr. of units in pkg. 1 Package weight(Lbs) 4.56000000000000005 Returnability N			ific user s
Range of product Product or component type Complete control station Device short name KY Provided equipment Contact block Legend plate Contact block name KA1 Complementary Enclosure/Cubicle description Surface mounting Enclosure material Die cast zinc alloy, colour : grey Type of installation Control station composition 2 push-buttons with 3 NO + 3 NC contacts FORWARD-REVERSE-STOP Connections - terminals Screw-clamp terminals [le] rated operational current AC In A Cordering and shipping details Crategory 21426 - 9001 K (NOT KA,KM,KX) Discount Schedule CS1 GTIN 00785901513414 Nbr. of units in pkg. 1 Package weight(Lbs) 4.56000000000000005 Returnability NY MY MY Provided equipment KY Complete control station Contact block Legend plate	Main		Space
Product or component type Complete control station Device short name KY Provided equipment Contact block Legend plate Contact block name KA1 Complementary Enclosure/Cubicle description Surface mounting Enclosure material Die cast zinc alloy, colour : grey Type of installation Indoor/Outdoor Control station composition 2 push-buttons with 3 NO + 3 NC contacts FORWARD-REVERSE-STOP Connections - terminals Screw-clamp terminals [le] rated operational current AC 10 A Environment NEMA degree of protection NEMA 3/4/13 Ordering and shipping details Category 21426 - 9001 K (NOT KA,KM,KX) Discount Schedule CS1 GTIN 00785901513414 Nbr. of units in pkg. 1 Package weight(Lbs) 4.560000000000005 Returnability N	Range of product	Harmony 9001K	ts for
Device short name KY Provided equipment Contact block Legend plate Contact block name KA1 Complementary Enclosure/Cubicle description Surface mounting Enclosure material Die cast zinc alloy, colour : grey Type of installation Indoor/Outdoor Control station composition 2 push-buttons with 3 NO + 3 NC contacts FORWARD-REVERSE-STOP Connections - terminals Screw-clamp terminals [le] rated operational current AC 10 A Environment NEMA degree of protection NEMA 3/4/13 Ordering and shipping details Category 21426 - 9001 K (NOT KA,KM,KX) Discount Schedule CS1 GTIN 00785901513414 Nbr. of units in pkg. 1 Package weight(Lbs) 4.5600000000000005 Returnability N	Product or component type	Complete control station	
Provided equipment Contact block Legend plate Contact block name KA1 Complementary Enclosure/Cubicle description Surface mounting Enclosure material Die cast zinc alloy, colour : grey Type of installation Control station composition Control station composition Control station composition Connections - terminals Screw-clamp terminals [le] rated operational current AC ID A Environment NEMA degree of protection NEMA 3/4/13 Ordering and shipping details Category 21426 - 9001 K (NOT KA,KM,KX) Discount Schedule CS1 GTIN 00785901513414 Nbr. of units in pkg. 1 Package weight(Lbs) 4.56000000000000005 Environment NEMA degree of protection NEMA MA August A, A, A, Contacts FORWARD-REVERSE-STOP BROWN CONTROL CO	Device short name	KY	α • «
Control block name KA1 Complementary Enclosure/Cubicle description Surface mounting Enclosure material Die cast zinc alloy, colour : grey Type of installation Indoor/Outdoor Control station composition 2 push-buttons with 3 NO + 3 NC contacts FORWARD-REVERSE-STOP Connections - terminals Screw-clamp terminals [le] rated operational current AC 10 A Environment NEMA degree of protection NEMA 3/4/13 Ordering and shipping details Category 21426 - 9001 K (NOT KA,KM,KX) Discount Schedule CS1 GTIN 00785901513414 Nbr. of units in pkg. 1 Package weight(Lbs) 4.5600000000000005 Environment NEMA ordering AS AS AS AS AS AS AS AS AS A	Provided equipment		ility of the
Complementary Enclosure/Cubicle description Enclosure material Die cast zinc alloy, colour : grey Type of installation Indoor/Outdoor Control station composition 2 push-buttons with 3 NO + 3 NC contacts FORWARD-REVERSE-STOP Connections - terminals Screw-clamp terminals [le] rated operational current AC 10 A Environment NEMA degree of protection NEMA 3/4/13 Ordering and shipping details Category 21426 - 9001 K (NOT KA,KM,KX) Discount Schedule CS1 GTIN 00785901513414 Nbr. of units in pkg. 1 Package weight(Lbs) 4.56000000000000005 Returnability N	Contact block name	KA1	reliab
Complementary Enclosure/Cubicle description Surface mounting Enclosure material Die cast zinc alloy, colour : grey Type of installation Indoor/Outdoor Control station composition 2 push-buttons with 3 NO + 3 NC contacts FORWARD-REVERSE-STOP Connections - terminals Screw-clamp terminals [le] rated operational current AC 10 A Environment NEMA degree of protection NEMA 3/4/13 Ordering and shipping details Category 21426 - 9001 K (NOT KA,KM,KX) Discount Schedule CS1 GTIN 00785901513414 Nbr. of units in pkg. 1 Package weight(Lbs) 4.56000000000000005 Returnability N			•
Enclosure/Cubicle description Enclosure material Die cast zinc alloy, colour : grey Type of installation Indoor/Outdoor Control station composition 2 push-buttons with 3 NO + 3 NC contacts FORWARD-REVERSE-STOP Connections - terminals [le] rated operational current AC IO A Environment NEMA degree of protection NEMA 3/4/13 Ordering and shipping details Category 21426 - 9001 K (NOT KA,KM,KX) Discount Schedule CS1 GTIN 00785901513414 Nbr. of units in pkg. 1 Package weight(Lbs) Returnability N Country of origin MX	Complementary		uitabil
Enclosure material Die cast zinc alloy, colour : grey Type of installation Indoor/Outdoor Control station composition 2 push-buttons with 3 NO + 3 NC contacts FORWARD-REVERSE-STOP Connections - terminals Screw-clamp terminals [le] rated operational current AC 10 A Environment NEMA degree of protection NEMA 3/4/13 Ordering and shipping details Category 21426 - 9001 K (NOT KA,KM,KX) Discount Schedule CS1 GTIN 00785901513414 Nbr. of units in pkg. 1 Package weight(Lbs) Returnability N Country of origin MX		Surface mounting	
Type of installation Indoor/Outdoor Control station composition 2 push-buttons with 3 NO + 3 NC contacts FORWARD-REVERSE-STOP Connections - terminals Screw-clamp terminals [le] rated operational current AC 10 A Environment NEMA degree of protection NEMA 3/4/13 Ordering and shipping details Category 21426 - 9001 K (NOT KA,KM,KX) Discount Schedule CS1 GTIN 00785901513414 Nbr. of units in pkg. 1 Package weight(Lbs) 4.5600000000000005 Returnability N Country of cricin MX	Enclosure material	Die cast zinc alloy, colour : grey	
Control station composition 2 push-buttons with 3 NO + 3 NC contacts FORWARD-REVERSE-STOP Connections - terminals [le] rated operational current AC 10 A Environment NEMA degree of protection NEMA 3/4/13 Ordering and shipping details Category 21426 - 9001 K (NOT KA,KM,KX) Discount Schedule CS1 GTIN 00785901513414 Nbr. of units in pkg. 1 Package weight(Lbs) 4.56000000000000005 Returnability N Country of origin MX	Type of installation	Indoor/Outdoor	
Connections - terminals [le] rated operational current AC 10 A Environment NEMA degree of protection NEMA 3/4/13 Ordering and shipping details Category 21426 - 9001 K (NOT KA,KM,KX) Discount Schedule CS1 GTIN 00785901513414 Nbr. of units in pkg. 1 Package weight(Lbs) Returnability N Country of origin MX	Control station composition	2 push-buttons with 3 NO + 3 NC contacts FORWARD-REVERSE-STOP	sed for
[le] rated operational current AC 10 A Environment NEMA degree of protection NEMA 3/4/13 Ordering and shipping details Category 21426 - 9001 K (NOT KA,KM,KX) Discount Schedule CS1 GTIN 00785901513414 Nbr. of units in pkg. 1 Package weight(Lbs) 4.560000000000005 Returnability N Country of origin MX	Connections - terminals	Screw-clamp terminals	n
Environment NEMA 3/4/13 Package weight(Lbs) Nema 3/4/14 Nema 3/4/15 Nema 3	[le] rated operational current AC	10 A	t
Environment NEMA degree of protection NEMA 3/4/13 Ordering and shipping details People of protection Category 21426 - 9001 K (NOT KA,KM,KX) Discount Schedule CS1 GTIN 00785901513414 Nbr. of units in pkg. 1 Package weight(Lbs) 4.56000000000000005 Returnability N Country of origin MX			<u>.s</u>
NEMA degree of protection NEMA 3/4/13 Ordering and shipping details Category 21426 - 9001 K (NOT KA,KM,KX) Discount Schedule CS1 GTIN 00785901513414 Nbr. of units in pkg. 1 Package weight(Lbs) 4.560000000000005 Returnability N Country of origin MX	Environment		for a
Ordering and shipping details Category 21426 - 9001 K (NOT KA,KM,KX) Discount Schedule CS1 GTIN 00785901513414 Nbr. of units in pkg. 1 Package weight(Lbs) 4.5600000000000005 Returnability N Country of origin MX		NEMA 3/4/13	titute——————————————————————————————————
Ordering and shipping details Category 21426 - 9001 K (NOT KA,KM,KX) Discount Schedule CS1 GTIN 00785901513414 Nbr. of units in pkg. 1 Package weight(Lbs) 4.5600000000000005 Returnability N Country of origin MX			sqns
Ordering and shipping details Security 21426 - 9001 K (NOT KA,KM,KX) Discount Schedule CS1 GTIN 00785901513414 Nbr. of units in pkg. 1 Package weight(Lbs) 4.5600000000000005 Returnability N Country of origin MX			as S
Discount Schedule CS1 CS		04400 00041/ (MOT1/A MAT/A)	
GTIN			ot
Nbr. of units in pkg. 1 Package weight(Lbs) 4.56000000000005 Returnability N E Country of origin MX			
Nor. of units in pkg. 1 Package weight(Lbs) 4.560000000000005 Returnability N Country of origin MX			
Returnability N Country of origin MX			
Returnability N Country of origin MX			oop •
Country of origin MX			 :
Education of original and the second of the second of the second or second o	Country of origin	MX	<u>a</u>
N 27 2047			

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1230 - Schneider Electric declaration of conformity
	Schneider Electric declaration of conformity
REACh	Reference not containing SVHC above the threshold
	Reference not containing SVHC above the threshold
Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations

Contractual warranty

Warranty period	18 months