# Product data sheet Characteristics

# 9070T750D5 INDUSTRIAL CONTROL TRANSFORMER 750VA MULTIPLE VOLTAGES

Product availability: Stock - Normally stocked in distribution facility





Price\*: 665.00 USD



#### Main

IVIAIII		<u> </u>
Product or component type	Industrial Control Transformer	7
Rated power in VA	500 VA	9
·	750 VA	₹
Primary voltage	600 V	
	575 V	<u></u>
	550 V	<u>,                                    </u>
Secondary voltage 120 V 115 V 110 V	120 V	<u> </u>
	115 V	. <del>.</del>
	110 V	
Range of product	Т	

## Complementary

Phase	1 phase	
Rated power in VA	750 VA per UL	
	750 VA per CSA	
	750 VA per NOM	
	500 VA per CE	
Primary voltage	550 V : 110 V	
	575 V : 115 V	
	600 V : 120 V	
Temperature rise	115 °C	
Electrical connection	Screw clamp terminals	
Height	4.51 in	
Width	5.25 in	
Depth	5.61 in	
Material	Copper winding	
Product compatibility	FSC2	

#### Environment

Product certifications	CE UL listed file E61239 CSA file LR37055 guide 184-N-90
NEMA degree of protection	Not rated (open device)
Insulation temperature	356 °F (180 °C)

## Ordering and shipping details

Category	16201 - 9070 T (NOT TF) 250-2000VA
Discount Schedule	CP8
GTIN	00785901739036
Nbr. of units in pkg.	1
Package weight(Lbs)	18.14000000000001
Returnability	Y
Country of origin	US

## Offer Sustainability

Sustainable offer status	Green Premium product	
RoHS (date code: YYWW)	Compliant - since 1227 - Schneider Electric declaration of conformity	
	Schneider Electric declaration of conformity	
REACh	Reference not containing SVHC above the threshold	
	Reference not containing SVHC above the threshold	
Product environmental profile	Available	
Product end of life instructions	Need no specific recycling operations	

#### Contractual warranty

Contraction Warranty		
Warranty period	18 months	