A9XPH112

Acti 9 - comb busbar - 1L - 18 mm pitch - 12 modules - 100A





Main Range Acti 9 Product or component type Accessory / separate part category Lines description 1L Length in 18 mm 12 modules

Complementary

Complementary	
Number of ways	12 ways 1 L
Poles configuration for 1 way	1 x 1P
Connection pitch	0.71 in (18 mm)
Connector type	tooth
Distance between way	0.71 in (18 mm)
Marking	L
Insulation	Insulated
Device presentation	Cuttable
[le] rated operational current	100 A 104 °F (40 °C)
[Ue] rated operational voltage	415 V AC
[Ui] rated insulation voltage	500 V AC IEC 61439-2
Mounting mode	Horizontal
Mounting location	Top or bottom tunnel type terminals Top or bottom double terminal
9 mm pitches	24
Maximum Width	8.66 in (220 mm)
Color	White RAL 9003)
Range compatibility	Acti 9 iC60 Acti 9 iK60 Acti 9 iK60 Acti 9 iID Acti 9 iID K Acti 9 iSW Acti 9 iSW-NA Multi 9 C60

Environment

IEC 60947-7-1 IEC 61439-2
1760 °F (960 °C) 30 s) IEC 60695-2-1
3 IEC 60947-7-1
IP20 with end-pieces and tooth covers

Ordering and shipping details

Category	00908 - C60N SUPPLEMENTARY PROTECTORS
Discount Schedule	DE2
GTIN	00785901953098
Nbr. of units in pkg.	1
Package weight(Lbs)	0.11 lb(US) (0.05 kg)
Returnability	Yes
Country of origin	DE

Packing Units

Package 1 Height	0.500 dm	
Package 1 width	0.300 dm	
Package 1 Length	2.100 dm	

Offer Sustainability

Sustainable offer status	Green Premium product
REACh free of SVHC	Yes
EU RoHS Directive	Compliant E EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	₽¥Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

Contractual warranty

	√
Warranty	18 months