## Product data sheet Characteristics

# **DTU321** SW NOT FUSIBLE DT 240VAC 30A 3P NEMA1

Product availability: Stock - Normally stocked in distribution facility





Price\*: 804.00 USD



#### Main

Product or component type	Double Throw Safety Switch	
Line Rated Current	30 A	_
Product certifications	UL listed	
NEMA degree of protection	NEMA 1 steel	_;
Device composition	None	_
Disconnector device type	Non-fusible disconnect	
Device mounting	Surface	_
Number of poles	3	_
System Voltage	240 V AC 250 V DC	_
AWG gauge	AWG 12AWG 2 (aluminium) AWG 14AWG 2 (copper)	

#### Ordering and shipping details

Main       Product or component type     Double Throw Safety Switch       Line Rated Current     30 A       Product certifications     UL listed       NEMA degree of protection     NEMA 1 steel       Device composition     None       Disconnector device type     Non-fusible disconnect       Device mounting     Surface       Number of poles     3       System Voltage     240 V AC       250 V DC       AWG gauge     AWG 12AWG 2 (aluminium)       AWG 14AWG 2 (copper)       Ordering and shipping details       Category     00033 - DT SWITCH,NEMA1       Discount Schedule     DE1       GTIN     00785901174530       Nbr. of units in pkg.     1       Package weight(Lbs)     35.039999999999999       Returnability     Y       Country of origin     US       Offer Sustainability       Sustainable offer status     Green Premium product       RoHS (date code: YYWW)     Compliant - since 1313 - Schneider Electric declaration of conformity       FEACh     Reference not containing SVHC above the threshold	3),		
Line Rated Current 30 A Product certifications UL listed  NEMA degree of protection NEMA 1 steel Device composition None Disconnector device type Non-fusible disconnect Device mounting Surface Number of poles 3 System Voltage 240 V AC 250 V DC AWG gauge AWG 12AWG 2 (aluminium) AWG 14AWG 2 (copper)  Ordering and shipping details Category 00033 - DT SWITCH, NEMA1 Discount Schedule DE1 GTIN 00785901174530 Nbr. of units in pkg. 1 Package weight(Lbs) 35.0399999999999 Returnability Y Country of origin US  Offer Sustainability Sustainable offer status Green Premium product RoHS (date code: YYWW) Compliant - since 1313 - Schneider Electric declaration of conformity	Main		
Product certifications  UL listed  NEMA degree of protection  NEMA 1 steel  Device composition  None  Disconnector device type  Non-fusible disconnect  Device mounting  Surface  Number of poles  3  System Voltage  AWG 12AWG 2 (aluminium)  AWG 14AWG 2 (copper)  Ordering and shipping details  Category  O0033 - DT SWITCH,NEMA1  Discount Schedule  DE1  GTIN  00785901174530  Nbr. of units in pkg.  1  Package weight(Lbs)  35.0399999999999  Returnability  Y  Country of origin  US  Offer Sustainability  Sustainable offer status  Green Premium product  Compliant - since 1313 - Schneider Electric declaration of conformity  Listing Augustical Augustic Augus	Product or component type	Double Throw Safety Switch	
NEMA degree of protection  NEMA 1 steel  Device composition  None  Disconnector device type  Non-fusible disconnect  Device mounting  Surface  Number of poles  3  System Voltage  AWG 12AWG 2 (aluminium) AWG 14AWG 2 (copper)  Ordering and shipping details  Category  Ordering and shipping details  Category  DE1  GTIN  00785901174530  Nbr. of units in pkg.  1  Package weight(Lbs)  35.0399999999999  Returnability  Y  Country of origin  US  Offer Sustainability  Sustainable offer status  Green Premium product  Compliant - since 1313 - Schneider Electric declaration of conformity  Schneider Electric declaration of conformity	Line Rated Current	30 A	
Device composition None  Disconnector device type Non-fusible disconnect  Device mounting Surface  Number of poles 3  System Voltage 240 V AC 250 V DC  AWG gauge AWG 12AWG 2 (aluminium) AWG 14AWG 2 (copper)  Ordering and shipping details  Category 00033 - DT SWITCH,NEMA1  Discount Schedule DE1  GTIN 00785901174530  Nbr. of units in pkg. 1  Package weight(Lbs) 35.0399999999999  Returnability Y  Country of origin US  Offer Sustainability  Sustainable offer status Green Premium product  RoHS (date code: YYWW) Compliant - since 1313 - Schneider Electric declaration of conformity  Schneider Electric declaration of conformity	Product certifications	UL listed	
Disconnector device type  Non-fusible disconnect  Device mounting  Surface  Number of poles  3  System Voltage  240 V AC 250 V DC  AWG gauge  AWG 12AWG 2 (aluminium) AWG 14AWG 2 (copper)  Ordering and shipping details  Category  00033 - DT SWITCH,NEMA1  Discount Schedule  DE1  GTIN  00785901174530  Nbr. of units in pkg.  1  Package weight(Lbs)  35.0399999999999  Returnability  Y  Country of origin  US  Offer Sustainability  Sustainable offer status  Green Premium product  RoHS (date code: YYWW)  Compliant - since 1313 - Schneider Electric declaration of conformity  Schneider Electric declaration of conformity	NEMA degree of protection	NEMA 1 steel	
Device mounting       Surface         Number of poles       3         System Voltage       240 V AC 250 V DC         AWG gauge       AWG 12AWG 2 (aluminium) AWG 14AWG 2 (copper)         Ordering and shipping details         Category       00033 - DT SWITCH,NEMA1         Discount Schedule       DE1         GTIN       00785901174530         Nbr. of units in pkg.       1         Package weight(Lbs)       35.0399999999999         Returnability       Y         Country of origin       US         Offer Sustainability         Sustainable offer status       Green Premium product         RoHS (date code: YYWW)       Compliant - since 1313 - Schneider Electric declaration of conformity	Device composition	None	
Number of poles  System Voltage  240 V AC 250 V DC  AWG gauge  AWG 12AWG 2 (aluminium) AWG 14AWG 2 (copper)  Ordering and shipping details  Category  00033 - DT SWITCH,NEMA1  Discount Schedule  DE1  GTIN  00785901174530  Nbr. of units in pkg.  1  Package weight(Lbs)  35.03999999999999  Returnability  Y  Country of origin  US  Offer Sustainability  Sustainable offer status  Green Premium product  ROHS (date code: YYWW)  Compliant - since 1313 - Schneider Electric declaration of conformity	Disconnector device type	Non-fusible disconnect	
System Voltage  240 V AC 250 V DC  AWG gauge  AWG 12AWG 2 (aluminium) AWG 14AWG 2 (copper)  Ordering and shipping details  Category  00033 - DT SWITCH,NEMA1  Discount Schedule  DE1  GTIN  00785901174530  Nbr. of units in pkg.  1 Package weight(Lbs)  35.03999999999999  Returnability  Y  Country of origin  US  Offer Sustainability  Sustainable offer status  Green Premium product  RoHS (date code: YYWW)  Compliant - since 1313 - Schneider Electric declaration of conformity	Device mounting	Surface	
AWG gauge  AWG 12AWG 2 (aluminium) AWG 14AWG 2 (copper)  Ordering and shipping details  Category  00033 - DT SWITCH,NEMA1  Discount Schedule  DE1  GTIN  00785901174530  Nbr. of units in pkg.  1  Package weight(Lbs)  35.03999999999999  Returnability  Y  Country of origin  US  Offer Sustainability  Sustainable offer status  Green Premium product  RoHS (date code: YYWW)  Compliant - since 1313 - Schneider Electric declaration of conformity	Number of poles	3	
AWG 14AWG 2 (copper)  Ordering and shipping details  Category 00033 - DT SWITCH,NEMA1  Discount Schedule DE1  GTIN 00785901174530  Nbr. of units in pkg. 1  Package weight(Lbs) 35.0399999999999999999999999999999999999	System Voltage		
Category 00033 - DT SWITCH,NEMA1  Discount Schedule DE1  GTIN 00785901174530  Nbr. of units in pkg. 1  Package weight(Lbs) 35.0399999999999999999999999999999999999	AWG gauge		
GTIN       00785901174530         Nbr. of units in pkg.       1         Package weight(Lbs)       35.0399999999999999999999999999999999999			
Nbr. of units in pkg. 1  Package weight(Lbs) 35.0399999999999999999999999999999999999	Discount Schedule	DE1	
Package weight(Lbs)  Returnability  Y  Country of origin  US  Offer Sustainability  Sustainable offer status  RoHS (date code: YYWW)  Compliant - since 1313 - Schneider Electric declaration of conformity  Schneider Electric declaration of conformity	GTIN	00785901174530	
Returnability  Country of origin  US  Offer Sustainability  Sustainable offer status  Green Premium product  RoHS (date code: YYWW)  Compliant - since 1313 - Schneider Electric declaration of conformity  Schneider Electric declaration of conformity	Nbr. of units in pkg.	1	
Country of origin  US  Offer Sustainability  Sustainable offer status  Green Premium product  RoHS (date code: YYWW)  Compliant - since 1313 - Schneider Electric declaration of conformity  Schneider Electric declaration of conformity	Package weight(Lbs)	35.0399999999999	
Offer Sustainability Sustainable offer status  RoHS (date code: YYWW)  Compliant - since 1313 - Schneider Electric declaration of conformity  Schneider Electric declaration of conformity	Returnability	Υ	
Sustainable offer status  Green Premium product  Compliant - since 1313 - Schneider Electric declaration of conformity  Schneider Electric declaration of conformity	Country of origin	US	
RoHS (date code: YYWW)  Compliant - since 1313 - Schneider Electric declaration of conformity  Schneider Electric declaration of conformity	Offer Sustainability		
Schneider Electric declaration of conformity	Sustainable offer status	Green Premium product	
-	RoHS (date code: YYWW)	Compliant - since 1313 - Schneider Electric declaration of conformity	
REACh Reference not containing SVHC above the threshold		Schneider Electric declaration of conformity	
	REACh	Reference not containing SVHC above the threshold	

## Offer Sustainability

Sustainable offer status	Green Premium product	
RoHS (date code: YYWW)	Compliant - since 1313 - Schneider Electric declaration of conformity	
	Schneider Electric declaration of conformity	É
REACh	Reference not containing SVHC above the threshold	

## Reference not containing SVHC above the threshold

Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations
Contractual warranty	
Warranty period	18 months