

Product availability : Stock - Normally stocked in distribution facility

Price\* : 536.00 USD



### Main

Range	TeSys
Product name	TeSys GS
Device short name	GS2JU
Product or component type	Switch-disconnector-fuse
Device application	Protection
Poles description	3P
Protected poles description	3t
Contacts type and composition	3 NO
[I <sub>th</sub> ] conventional free air thermal current	100 A at 104 °F (40 °C)
[I <sub>e</sub> ] rated operational current	100 A
Fuse type	UL
Fuse size	J
Network type	AC DC
Network frequency	50/60 Hz

### Complementary

Type of operating handle	External frontal
Mounting support	Plate
[U <sub>i</sub> ] rated insulation voltage	750 V
[U <sub>imp</sub> ] rated impulse withstand voltage	8 kV
Rated operational power in W	90 kW at 690 V 63 kW at 500 V 51 kW at 400 V
Short-circuit withstand	22 kA
Mechanical durability	10000 cycles

Connections - terminals	Power circuit: bars cable 34...42 mm <sup>2</sup> Lugs-ring terminals
Tightening torque	Power circuit: 35.4 lbf.in (4 N.m)

## Environment

Standards	CSA C22.2 No 4 UL98
IP degree of protection	IP20 with terminal cover conforming to IEC 60529
Ambient air temperature for operation	-4...158 °F (-20...70 °C)
Ambient air temperature for storage	-40...176 °F (-40...80 °C)
Fire resistance	1760 °F (960 °C) body
Height	7.32 in (186 mm)
Width	5.88 in (149.3 mm)
Depth	122.2 mm
Product weight	6.09 lb(US) (2.761 kg)

## Ordering and shipping details

Category	22640 - IEC DISCONNECT-GS1,LK3
Discount Schedule	I11
GTIN	00785901547686
Nbr. of units in pkg.	1
Package weight(Lbs)	5.1000000000000005
Returnability	Y
Country of origin	FR

## Offer Sustainability

Sustainable offer status	Not Green Premium product
REACH	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold

## Contractual warranty

Warranty period	18 months
-----------------	-----------