

Main

Disconnecter device type	Fusible disconnect switch
Enclosure type	Enclosure rainproof indoor/outdoor Enclosure ice/sleet proof indoor/outdoor
Series name	Heavy duty

Complementary

Rated current	30 A
AWG gauge	AWG 14...AWG 6 copper AWG 12...AWG 6 aluminium
Device composition	Neutral (factory installed)
Device mounting	Surface
Electrical connection	Lugs
Enclosure material	Galvannealed steel
Interlocking type	Without electrical interlock
Number of poles	2
Permissible voltage	<= 240 V AC <= 250 V DC
Short-circuit protection	200 kA R or J 10 kA H or K
Switch function	TPST

Environment

NEMA degree of protection	NEMA 3R
product certifications	UL listed

Offer Sustainability

Not Green Premium product	Not Green Premium product
Will be Compliant on 3Q2014	Will be Compliant on 3Q2014 Will be Compliant on 3Q2014
Reference not containing SVHC above the threshold	Reference not containing SVHC above the threshold
WARNING: This product can expose you to chemicals including:	WARNING: This product can expose you to chemicals including:
Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm.	Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm.
For more information go to www.p65warnings.ca.gov	For more information go to www.p65warnings.ca.gov

Contractual warranty

Warranty period	18 months
-----------------	-----------