## Product data sheet Characteristics

# H361SS SW FUSIBLE HD 30A 3P NEMA 4 4X 5 316 SS

Product availability: Stock - Normally stocked in distribution facility





Price\*: 3444.00 USD



### Main

| 3                             |   |  |  |
|-------------------------------|---|--|--|
|                               |   |  |  |
|                               |   |  |  |
| Main                          |   |  |  |
| Product or component type     | Single Throw Safety Switch                      |  |  |
| Line Rated Current            | 30 A  |  |  |
| Product certifications        | UL listed                                       |  |  |
| NEMA degree of protection     | NEMA 3/3R4/4X/12 stainless steel 316            |  |  |
| Device composition            | None  |  |  |
| Disconnector device type      | Fusible disconnect                              |  |  |
| Short-circuit current         | 10 kA H or K<br>200 kA R, J or L                |  |  |
| Device mounting               | Surface   |  |  |
| Number of poles               | 3   |  |  |
| Electrical connection         | Lugs  |  |  |
| Series name                   | Heavy duty                                      |  |  |
| System Voltage                | 600 V AC/DC                                     |  |  |
| AWG gauge                     | AWG 14AWG 6 (copper)<br>AWG 12AWG 6 (aluminium) |  |  |
|                               |   |  |  |
| Ordering and shipping details |   |  |  |
| Category                      | 00010 - H&HU SW 2&3P N4 SS 30-200A              |  |  |

#### Ordering and shipping details

| Oracing and shipping act | tano                               |       |
|--------------------------|------------------------------------|-------|
| Category                 | 00010 - H&HU SW,2&3P,N4,SS,30-200A |       |
| Discount Schedule        | DE1                                |       |
| GTIN                     | 00785901695578                     | pep   |
| Nbr. of units in pkg.    | 1                                  | inter |
| Package weight(Lbs)      | 13.52                              | s not |
| Returnability            | Υ                                  |       |
| Country of origin        | US                                 |       |

### Offer Sustainability

| Sustainable offer status | Green Premium product |
|--------------------------|-----------------------|

| RoHS (date code: YYWW)           | Compliant - since 1313 - Schneider Electric declaration of conformity  Schneider Electric declaration of conformity |  |
|----------------------------------|---|--|
| REACh                            | Reference not containing SVHC above the threshold   |  |
|                                  | Reference not containing SVHC above the threshold   |  |
| Product environmental profile    | Available   |  |
| Product end of life instructions | Need no specific recycling operations   |  |
| Contractual warranty             |   |  |
| Warranty period                  | 18 months   |  |