Product data sheet Characteristics

HOM1224L125PRB HOM OUTD 125A MLO 12/24CIR

Product availability: Stock - Normally stocked in distribution facility





Price*: 278.00 USD



Main

Iviaiii		
Product or component type	Load Center	
Range of product	Homeline	
Load center type	Main lugs	
Line Rated Current	125 A	
Number of spaces	12	
Number of circuits	24	
NEMA degree of protection	NEMA 3R outdoor	
Cover type	Surface cover	
Electrical connection	Lugs	

Complementary

Short-circuit current	10 kA	
Number of tandem circuit breakers	12	
Phase	1 phase	
System Voltage	120/240 V AC	
AWG gauge	AWG 6AWG 2/0 [Space(aluminium) AWG 6AWG 1 [Space(copper)	
Wiring configuration	3-wire	
Cover finish	Gray baked enamel	
Material	Tin plated aluminium busbar	
Enclosure material	Welded galvannealed steel	
Surface finish	Baked enamel grey	
Box number	3R	

Environment

Product certifications	UL E-6294

Ordering and shipping details

Category	00145 - HOM LC&CVR,12-42CKT NEMA3R
Discount Schedule	DE3C
GTIN	00785901863670
Nbr. of units in pkg.	1
Package weight(Lbs)	20.75
Returnability	Υ
Country of origin	US

Offer Sustainability

Green Premium product	
Compliant - since 1414 - Schneider Electric declaration of conformity	
Schneider Electric declaration of conformity	
Reference not containing SVHC above the threshold	
Reference not containing SVHC above the threshold	
Available	
Need no specific recycling operations	