Product data sheet Characteristics

HOM2040M200PCVP HOM VALPK INDR 200A MB 20/40CIR

Product availability: Stock - Normally stocked in distribution facility





Price*: 925.65 USD



Main

Range of product Homeline Load center type Main breaker Line Rated Current 200 A Number of spaces 20 Number of circuits 40 NEMA degree of protection NEMA 1 indoor Cover type Combination flush/surface cover Electrical connection Lugs			
Load center type Main breaker Line Rated Current 200 A Number of spaces 20 Number of circuits 40 NEMA degree of protection NEMA 1 indoor Cover type Combination flush/surface cover Electrical connection Lugs Provided equipment Circuit breaker [Space(1) 2P 200 A 120/240 V AC main supply ready assembled Circuit breaker [Space(3) 1P 20 A 120/240 V AC	Product or component type	Load Center	
Line Rated Current 200 A Number of spaces 20 Number of circuits 40 NEMA degree of protection NEMA 1 indoor Cover type Combination flush/surface cover Electrical connection Lugs Provided equipment Circuit breaker [Space(1) 2P 200 A 120/240 V AC main supply ready assembled Circuit breaker [Space(3) 1P 20 A 120/240 V AC	Range of product	Homeline	
Number of spaces 20 Number of circuits 40 NEMA degree of protection NEMA 1 indoor Cover type Combination flush/surface cover Electrical connection Lugs Provided equipment Circuit breaker [Space(1) 2P 200 A 120/240 V AC main supply ready assembled Circuit breaker [Space(3) 1P 20 A 120/240 V AC	Load center type	Main breaker	
Number of circuits 40 NEMA degree of protection NEMA 1 indoor Cover type Combination flush/surface cover Electrical connection Lugs Provided equipment Circuit breaker [Space(1) 2P 200 A 120/240 V AC main supply ready assembled Circuit breaker [Space(3) 1P 20 A 120/240 V AC	Line Rated Current	200 A	
NEMA degree of protection NEMA 1 indoor Cover type Combination flush/surface cover Electrical connection Lugs Provided equipment Circuit breaker [Space(1) 2P 200 A 120/240 V AC main supply ready assembled Circuit breaker [Space(3) 1P 20 A 120/240 V AC	Number of spaces	20	
Cover type Combination flush/surface cover Electrical connection Lugs Provided equipment Circuit breaker [Space(1) 2P 200 A 120/240 V AC main supply ready assembled Circuit breaker [Space(3) 1P 20 A 120/240 V AC	Number of circuits	40	
Electrical connection Lugs Provided equipment Circuit breaker [Space(1) 2P 200 A 120/240 V AC main supply ready assembled Circuit breaker [Space(3) 1P 20 A 120/240 V AC	NEMA degree of protection	NEMA 1 indoor	
Provided equipment Circuit breaker [Space(1) 2P 200 A 120/240 V AC main supply ready assembled Circuit breaker [Space(3) 1P 20 A 120/240 V AC	Cover type	Combination flush/surface cover	
Circuit breaker [Space(3) 1P 20 A 120/240 V AC	Electrical connection	Lugs	
	Provided equipment	Circuit breaker [Space(3) 1P 20 A 120/240 V AC	

Complementary

-		
Main		
Product or component type	Load Center	
Range of product	Homeline	
Load center type	Main breaker	
Line Rated Current	200 A	
Number of spaces	20	
Number of circuits	40	
NEMA degree of protection	NEMA 1 indoor	
Cover type	Combination flush/surface cover	
Electrical connection	Lugs	
Liooti loai comiliootion	Lugs	
Provided equipment	Circuit breaker [Space(1) 2P 200 A 120/240 V AC main supply ready assembled Circuit breaker [Space(3) 1P 20 A 120/240 V AC Circuit breaker [Space(2) 2P 30 A 120/240 V AC	
Provided equipment	Circuit breaker [Space(1) 2P 200 A 120/240 V AC main supply ready assembled Circuit breaker [Space(3) 1P 20 A 120/240 V AC	
Provided equipment Complementary Short-circuit current	Circuit breaker [Space(1) 2P 200 A 120/240 V AC main supply ready assembled Circuit breaker [Space(3) 1P 20 A 120/240 V AC Circuit breaker [Space(2) 2P 30 A 120/240 V AC	
Provided equipment Complementary Short-circuit current Number of tandem circuit breakers	Circuit breaker [Space(1) 2P 200 A 120/240 V AC main supply ready assembled Circuit breaker [Space(3) 1P 20 A 120/240 V AC Circuit breaker [Space(2) 2P 30 A 120/240 V AC	
Complementary Short-circuit current Number of tandem circuit breakers Phase	Circuit breaker [Space(1) 2P 200 A 120/240 V AC main supply ready assembled Circuit breaker [Space(3) 1P 20 A 120/240 V AC Circuit breaker [Space(2) 2P 30 A 120/240 V AC 22 kA 20	
Complementary Short-circuit current Number of tandem circuit breakers Phase System Voltage	Circuit breaker [Space(1) 2P 200 A 120/240 V AC main supply ready assembled Circuit breaker [Space(3) 1P 20 A 120/240 V AC Circuit breaker [Space(2) 2P 30 A 120/240 V AC 22 kA 20 1 phase	
Provided equipment Complementary Short-circuit current Number of tandem circuit breakers Phase System Voltage AWG gauge	Circuit breaker [Space(1) 2P 200 A 120/240 V AC main supply ready assembled Circuit breaker [Space(3) 1P 20 A 120/240 V AC Circuit breaker [Space(2) 2P 30 A 120/240 V AC 22 kA 20 1 phase 120/240 V AC	
Complementary Short-circuit current Number of tandem circuit breakers Phase System Voltage AWG gauge Wiring configuration	Circuit breaker [Space(1) 2P 200 A 120/240 V AC main supply ready assembled Circuit breaker [Space(3) 1P 20 A 120/240 V AC Circuit breaker [Space(2) 2P 30 A 120/240 V AC 22 kA 20 1 phase 120/240 V AC AWG 4250 kcmil aluminium/copper	
Complementary Short-circuit current Number of tandem circuit breakers Phase System Voltage AWG gauge Wiring configuration Material	Circuit breaker [Space(1) 2P 200 A 120/240 V AC main supply ready assembled Circuit breaker [Space(3) 1P 20 A 120/240 V AC Circuit breaker [Space(2) 2P 30 A 120/240 V AC 22 kA 20 1 phase 120/240 V AC AWG 4250 kcmil aluminium/copper 3-wire	
Complementary Short-circuit current Number of tandem circuit breakers Phase System Voltage AWG gauge Wiring configuration Material Enclosure material	Circuit breaker [Space(1) 2P 200 A 120/240 V AC main supply ready assembled Circuit breaker [Space(3) 1P 20 A 120/240 V AC Circuit breaker [Space(2) 2P 30 A 120/240 V AC 22 kA 20 1 phase 120/240 V AC AWG 4250 kcmil aluminium/copper 3-wire Tin plated aluminium busbar	
Provided equipment Complementary	Circuit breaker [Space(1) 2P 200 A 120/240 V AC main supply ready assembled Circuit breaker [Space(3) 1P 20 A 120/240 V AC Circuit breaker [Space(2) 2P 30 A 120/240 V AC 22 kA 20 1 phase 120/240 V AC AWG 4250 kcmil aluminium/copper 3-wire Tin plated aluminium busbar Welded sheet steel	
Complementary Short-circuit current Number of tandem circuit breakers Phase System Voltage AWG gauge Wiring configuration Material Enclosure material Cover finish	Circuit breaker [Space(1) 2P 200 A 120/240 V AC main supply ready assembled Circuit breaker [Space(3) 1P 20 A 120/240 V AC Circuit breaker [Space(2) 2P 30 A 120/240 V AC 22 kA 20 1 phase 120/240 V AC AWG 4250 kcmil aluminium/copper 3-wire Tin plated aluminium busbar Welded sheet steel Gray baked enamel	

Environment

Product certifications	UL E-6294

Ordering and shipping details

Category	00185 - MISC. HOM LOAD CENTERS
Discount Schedule	DE3C
GTIN	00785901977063
Nbr. of units in pkg.	1
Package weight(Lbs)	30.59
Returnability	Υ
Country of origin	US

Offer Sustainability

Sustainable offer status	Green Premium product	
RoHS (date code: YYWW)	Compliant - since 1414 - Schneider Electric declaration of conformity	
	Schneider Electric declaration of conformity	
REACh	Reference not containing SVHC above the threshold	
	Reference not containing SVHC above the threshold	
Product environmental profile	Available	
Product end of life instructions	Need no specific recycling operations	