Product data sheet Characteristics

HOM2448L125PRB HOM OUTD 125A MLO 24/48CIR

Product availability: Stock - Normally stocked in distribution facility





Price*: 390.00 USD



Main

IVICIII		· ·
Product or component type	Load Center	9
Range of product	Homeline	2
Load center type	Main lugs	
Line Rated Current	125 A	-
Number of spaces	24	; ;
Number of circuits	48	
NEMA degree of protection	NEMA 3R outdoor	4
Cover type	Surface cover	
Electrical connection	Lugs	

Complementary

		_
Short-circuit current	10 kA	9
Number of tandem circuit breakers	24	
Phase	1 phase	ton to
System Voltage	120/240 V AC	,- C
AWG gauge	AWG 6AWG 2/0 aluminium AWG 6AWG 1 copper	titute for
Wiring configuration	3-wire	<u>v</u>
Material	Tin plated aluminium busbar	
Enclosure material	Welded galvannealed steel	
Cover finish	Gray baked enamel	
Box number	6R	. <u>v</u>

Environment

Product certifications	UL E-6294		
------------------------	-----------	--	--

Ordering and shipping details

Category	00145 - HOM LC&CVR,12-42CKT NEMA3R
Discount Schedule	DE3C
GTIN	00785901977117
Nbr. of units in pkg.	1
Package weight(Lbs)	30.40000000000002
Returnability	Υ
Country of origin	US

Offer Sustainability

Sustainable offer status	Green Premium product	
RoHS (date code: YYWW)	Compliant - since 1414 - Schneider Electric declaration of conformity	
	Schneider Electric declaration of conformity	
REACh	Reference not containing SVHC above the threshold	
	Reference not containing SVHC above the threshold	
Product environmental profile	Available	
Product end of life instructions	Need no specific recycling operations	