Product data sheet Characteristics

HOM4080L225PGC HOM INDR 225A MLO 40/80CIR WGB

Product availability: Stock - Normally stocked in distribution facility





Price*: 671.00 USD



Main

Product or component type	Load Center
Range of product	Homeline
Load center type	Main lugs
Line Rated Current	225 A
Number of spaces	40
Number of circuits	80
NEMA degree of protection	NEMA 1 indoor
Cover type	Combination flush/surface cover
Electrical connection	Lugs
Provided equipment	Grounding bar [Space(1)

Complementary

Short-circuit current	10 kA
Number of tandem circuit breakers	40
Phase	1 phase
System Voltage	120/240 V AC
AWG gauge	AWG 4250 kcmil copper AWG 4300 kcmil aluminium
Wiring configuration	3-wire
Material	Tin plated aluminium busbar
Enclosure material	Welded sheet steel
Cover finish	Gray baked enamel
Box number	12

Environment

Product certifications	UL E-6294

Ordering and shipping details

Category	00045 - HOM LC&CVR,12-42 CKT,NEMA1
Discount Schedule	DE3C
GTIN	00785901978176
Nbr. of units in pkg.	1
Package weight(Lbs)	35.85000000000001
Returnability	Υ
Country of origin	US

Offer Sustainability

Sustainable offer status	Green Premium product	
RoHS (date code: YYWW)	Compliant - since 1414 - Schneider Electric declaration of conformity	
	Schneider Electric declaration of conformity	
REACh	Reference not containing SVHC above the threshold	
	Reference not containing SVHC above the threshold	
Product environmental profile	Available	
Product end of life instructions	Need no specific recycling operations	