Product data sheet Characteristics

HOM4080M200PC1AVP HOM 1AF VPK INDR 200A MB 40/80CIR

Product availability: Stock - Normally stocked in distribution facility





Price*: 1485.15 USD



Main

| Product or component type | Load Center |
|---------------------------|--|
| Range of product | Homeline |
| Load center type | Main breaker |
| Line Rated Current | 200 A |
| Number of spaces | 40 |
| Number of circuits | 80 |
| NEMA degree of protection | NEMA 1 indoor |
| Cover type | Combination flush/surface cover |
| Electrical connection | Lugs |
| Provided equipment | Circuit breaker [Space(3) 1P 20 A 120/240 V AC Circuit breaker [Space(2) 2P 30 A 120/240 V AC Arc fault circuit breaker [Space(1) 1P 15 A 120/240 V AC |
| | |

Complementary

| BW P | | |
|--|--|--|
| | | |
| Main | | |
| Product or component type | Load Center | |
| Range of product | Homeline | |
| Load center type | Main breaker | |
| Line Rated Current | 200 A | |
| Number of spaces | 40 | |
| Number of circuits | 80 | |
| NEMA degree of protection | NEMA 1 indoor | |
| Cover type | Combination flush/surface cover | |
| Electrical connection | Lugs | |
| | | |
| Provided equipment | Circuit breaker [Space(3) 1P 20 A 120/240 V AC Circuit breaker [Space(2) 2P 30 A 120/240 V AC Arc fault circuit breaker [Space(1) 1P 15 A 120/240 V AC | |
| Provided equipment Complementary Short-circuit current | Circuit breaker [Space(2) 2P 30 A 120/240 V AC | |
| Complementary Short-circuit current | Circuit breaker [Space(2) 2P 30 A 120/240 V AC Arc fault circuit breaker [Space(1) 1P 15 A 120/240 V AC | |
| Complementary Short-circuit current Number of tandem circuit breakers | Circuit breaker [Space(2) 2P 30 A 120/240 V AC Arc fault circuit breaker [Space(1) 1P 15 A 120/240 V AC 22 kA | |
| Complementary Short-circuit current Number of tandem circuit breakers Phase | Circuit breaker [Space(2) 2P 30 A 120/240 V AC Arc fault circuit breaker [Space(1) 1P 15 A 120/240 V AC 22 kA 40 | |
| Complementary Short-circuit current Number of tandem circuit breakers Phase System Voltage | Circuit breaker [Space(2) 2P 30 A 120/240 V AC Arc fault circuit breaker [Space(1) 1P 15 A 120/240 V AC 22 kA 40 1 phase | |
| Complementary Short-circuit current Number of tandem circuit breakers Phase System Voltage AWG gauge | Circuit breaker [Space(2) 2P 30 A 120/240 V AC Arc fault circuit breaker [Space(1) 1P 15 A 120/240 V AC 22 kA 40 1 phase 120/240 V AC | |
| Complementary Short-circuit current Number of tandem circuit breakers Phase System Voltage AWG gauge Wiring configuration | Circuit breaker [Space(2) 2P 30 A 120/240 V AC Arc fault circuit breaker [Space(1) 1P 15 A 120/240 V AC 22 kA 40 1 phase 120/240 V AC AWG 4250 kcmil aluminium/copper | |
| Complementary Short-circuit current Number of tandem circuit breakers Phase System Voltage AWG gauge Wiring configuration Material | Circuit breaker [Space(2) 2P 30 A 120/240 V AC Arc fault circuit breaker [Space(1) 1P 15 A 120/240 V AC 22 kA 40 1 phase 120/240 V AC AWG 4250 kcmil aluminium/copper 3-wire | |
| Complementary Short-circuit current Number of tandem circuit breakers Phase System Voltage AWG gauge Wiring configuration Material Enclosure material | Circuit breaker [Space(2) 2P 30 A 120/240 V AC Arc fault circuit breaker [Space(1) 1P 15 A 120/240 V AC 22 kA 40 1 phase 120/240 V AC AWG 4250 kcmil aluminium/copper 3-wire Tin plated aluminium busbar | |
| Complementary Short-circuit current Number of tandem circuit breakers Phase System Voltage AWG gauge Wiring configuration Material Enclosure material Cover finish | Circuit breaker [Space(2) 2P 30 A 120/240 V AC Arc fault circuit breaker [Space(1) 1P 15 A 120/240 V AC 22 kA 40 1 phase 120/240 V AC AWG 4250 kcmil aluminium/copper 3-wire Tin plated aluminium busbar Welded sheet steel | |
| Complementary | Circuit breaker [Space(2) 2P 30 A 120/240 V AC Arc fault circuit breaker [Space(1) 1P 15 A 120/240 V AC 22 kA 40 1 phase 120/240 V AC AWG 4250 kcmil aluminium/copper 3-wire Tin plated aluminium busbar Welded sheet steel Gray baked enamel | |

Environment

| Product certifications | UL E-6294 |
|------------------------|-----------|

Ordering and shipping details

| Category | 00185 - MISC. HOM LOAD CENTERS |
|-----------------------|--------------------------------|
| Discount Schedule | DE3C |
| GTIN | 00785901977049 |
| Nbr. of units in pkg. | 1 |
| Package weight(Lbs) | 40.52000000000003 |
| Returnability | Υ |
| Country of origin | US |

Offer Sustainability

| Green Premium product |
|---|
| Compliant - since 1414 - Schneider Electric declaration of conformity |
| Schneider Electric declaration of conformity |
| Reference not containing SVHC above the threshold |
| Reference not containing SVHC above the threshold |
| Available |
| Need no specific recycling operations |
| |