Product data sheet Characteristics

HU365DS SWITCH NONFUSIBLE HD 400A STAINLESS

Product availability: Stock - Normally stocked in distribution facility





Price*: 14294.00 USD



Main

Product or component type	Single Throw Safety Switch	
Line Rated Current	400 A	<u></u>
Product certifications	UL listed	
NEMA degree of protection	NEMA 3/3R4/4X/12 stainless steel 304	
Device composition	None	> =
Disconnector device type	Non-fusible disconnect	
Short-circuit current	200 kA maximum	
Device mounting	Surface	
Number of poles	3	v
Electrical connection	Lugs	. E
Series name	Heavy duty	<u>a</u>
System Voltage	600 V AC/DC	م م
AWG gauge	AWG 1/0750 kcmil (copper or aluminium)	

Ordering and shipping details

Category	00055 - H&HU SW,NEMA4&5,400-1200A	,
Discount Schedule	DE1	
GTIN	00785901195979	
Nbr. of units in pkg.	1	
Package weight(Lbs)	175	
Returnability	Υ	:
Country of origin	US	

Offer Sustainability

Sustainable offer status	Green Premium product	- vid
RoHS (date code: YYWW)	Compliant - since 1425 - Schneider Electric declaration of conformity	_ :

Schneider Electric declaration of conformity

REACh	Reference not containing SVHC above the threshold
	Reference not containing SVHC above the threshold
Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations
Contractual warranty	

Warranty period	 18 months