

LA36400

3P 400A 600V LA MOULDED CASE CIRCUIT BREAKER

Product availability : Stock - Normally stocked in distribution facility



Price* : 4944.00 USD



Main

| | |
|---------------------------|------------------|
| Product or component type | Circuit breaker |
| Range of product | I-Line |
| Trip unit technology | Thermal-magnetic |
| Breaking capacity code | A |

Complementary

| | |
|---------------------------|--|
| Line Rated Current | 400 A |
| Poles description | 3P |
| Breaking capacity | 25 kA at 600 V AC 42 kA at 240 V AC 30 kA at 480 V AC |
| System Voltage | 250 V DC 600 V AC |
| Mounting mode | I-Line |
| Electrical connection | I-Line connection line Lugs load |
| AWG gauge | AWG 1...600 kcmil (aluminium/copper) 1 cable(s) AWG 1...250 kcmil (aluminium/copper) 2 cable(s) |
| Terminal identifier | AL400LA |
| Magnetic hold current | 2000 A |
| Magnetic tripping current | 4000 A |
| Wiring configuration | 3-wire |
| Phase connection | ABC |

Environment

| | |
|------------------------|------------------|
| Product certifications | CSA UL listed |
|------------------------|------------------|

Ordering and shipping details

| | |
|-----------------------|----------------------------------|
| Category | 01040 - LA/LH BRKR, SW, MAG-GARD |
| Discount Schedule | DE2 |
| GTIN | 00785901426325 |
| Nbr. of units in pkg. | 1 |
| Package weight(Lbs) | 18.34 |
| Returnability | Y |
| Country of origin | MX |

Offer Sustainability

| | |
|----------------------------------|---|
| Sustainable offer status | Green Premium product |
| RoHS (date code: YYWW) | Compliant - since 1304 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity |
| REACH | Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold |
| Product environmental profile | Available |
| Product end of life instructions | Need no specific recycling operations |

Contractual warranty

| | |
|-----------------|-----------|
| Warranty period | 18 months |
|-----------------|-----------|