

LULC09

devicenet communication module - for TeSys U -
24 V DC

Product availability : Stock - Normally stocked in distribution facility

Price* : 218.00 USD



Main

Range	TeSys
Device short name	LUL
Product or component type	Communication module
Product compatibility	LUCA LUCB LUCC LUCD LUCL LUCM
Device application	Communication
Range compatibility	TeSys TeSys U LUB non reversing power base TeSys TeSys U LU2B reversing power base

Complementary

Function available	Communication module
Mounting mode	Plug-in
Mounting location	Front side
Physical interface	Open style connector
Bus type	DeviceNet
Communication port protocol	CAN2.0A CAN2.B
Addressing	0...63
Current consumption	1.5 mAat 24 V DC 20...28 V
Logic input	Positiveat 24 V DC - 7 mA
Response time	10 ms +/- 30 % change to state 0 10 ms +/- 30 % change to state 1
Input type	Resistive
Number of outputs	1

	2 dedicated to starter-controller coil operation
[Us] rated supply voltage	24 V DC
Output current	<= 500 mA
Protection type	GL fuse 2 A
Switching current capacity	0.5 mAat 24 V
Local signalling	3 LEDs front panel
Connection pitch	0.2 in (5 mm) open style DeviceNet 0.15 in (3.81 mm)
Connections - terminals	Screw clamp terminals 2 cable 0 in ² (0.75 mm ²) - cable stiffness: flexible - with cable end Screw clamp terminals 1 cable 0...0 in ² (0.14...1 mm ²) - cable stiffness: flexible - without cable end Screw clamp terminals 1 cable 0...0 in ² (0.14...1 mm ²) - cable stiffness: rigid - without cable end Screw clamp terminals 1 cable 0...0 in ² (0.25...0.5 mm ²) - cable stiffness: flexible - with cable end Screw clamp terminals 1 cable 0...0 in ² (0.25...1 mm ²) - cable stiffness: flexible - with cable end Screw clamp terminals 2 cable 0...0 in ² (0.14...0.5 mm ²) - cable stiffness: rigid - without cable end Screw clamp terminals 2 cable 0...0 in ² (0.14...0.75 mm ²) - cable stiffness: flexible - without cable end Screw clamp terminals 2 cable 0...0 in ² (0.25...0.34 mm ²) - cable stiffness: flexible - with cable end BUS 1 cable 0...0 in ² (0.2...2.5 mm ²) - cable stiffness: flexible - without cable end BUS 1 cable 0...0 in ² (0.2...2.5 mm ²) - cable stiffness: rigid - without cable end BUS 1 cable 0...0 in ² (0.25...2.5 mm ²) - cable stiffness: flexible - with cable end BUS 2 cable 0...0 in ² (0.14...0.5 mm ²) - cable stiffness: rigid - without cable end BUS 2 cable 0...0 in ² (0.25...1 mm ²) - cable stiffness: flexible - with cable end BUS 2 cable 0...0 in ² (0.5...1.5 mm ²) - cable stiffness: flexible - with cable end BUS 2 cable 0...0 in ² (0.5...1.5 mm ²) - cable stiffness: flexible - without cable end
Associated cable type	AWG 26...AWG 16 screw clamp terminals AWG24...AWG16 BUS
Tightening torque	1.77...2.21 lbf.in (0.2...0.25 N.m) flat Ø 2.5 mm 4.42...5.31 lbf.in (0.5...0.6 N.m) flat Ø 3.5 mm

Environment

Standards	IEC 62026-1
Ambient air temperature for operation	-13...131 °F (-25...55 °C)
IP degree of protection	IP20 IEC 60529

Ordering and shipping details

Category	22398 - TESYS U - MULTI-FCTN CTRL MOD(LUCM)
Discount Schedule	I11
GTIN	00785901684091
Nbr. of units in pkg.	1
Package weight(Lbs)	0.23999999999999999
Returnability	N
Country of origin	FR

Contractual warranty

Warranty period	18 months
-----------------	-----------