

Product availability : Stock - Normally stocked in distribution facility



Main

Product or component type	Enclosure
Range of product	QO
Enclosure type	Enclosure
Line Rated Current	125 A
Number of spaces	2
Short-circuit current	22 kA
Number of circuits	2
Number of tandem circuit breakers	0
Phase	1 phase

Complementary

AWG gauge	AWG 14...AWG 2/0 (copper) AWG 12...AWG 2/0 (aluminium)
NEMA degree of protection	NEMA 3R outdoor
Cover type	Surface cover
Device composition	Grounding bar (ordered separately)
Electrical connection	Lugs
Wiring configuration	3-wire
Material	Tin plated copper busbar
Enclosure material	Welded galvanized steel
Surface finish	Baked enamel grey
Box number	13R
Product certifications	UL listed
Height	411 mm
Width	6.93 in (176 mm)

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Ordering and shipping details

Category	00005 - QO,Q2L 2P ENCL & BREAKERS
Discount Schedule	DE2A
GTIN	00785901051800
Nbr. of units in pkg.	1
Package weight(Lbs)	9.8900000000000006
Returnability	Y
Country of origin	MX

Offer Sustainability

Sustainable offer status	Not Green Premium product
RoHS (date code: YYWW)	Compliant - since 0701 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold
Product end of life instructions	Need no specific recycling operations

Contractual warranty

Warranty period	18 months
-----------------	-----------