Product data sheet Characteristics

QU816D400SL METER MAIN 400A RINGLESS

Product availability: Stock - Normally stocked in distribution facility





Main

Product or component type	Meter Mains	
Range of product	QO	

Complementary

Line Rated Current	400 A	— ţ
Short-circuit current	25 kA	
Meter socket type	Ringless	
Device mounting	Surface	— tilide
Number of spaces	8	
Number of circuits	16	— i
Product mounting	Surface	defe
Number of tandem circuit breakers	8	
Hub type	A-L	— d
Electrical connection	Studs line side Feed-thru lugs service ground	_ not to b
AWG gauge	AWG 4250 kcmil (aluminium) service ground AWG 4250 kcmil (copper) service ground	for and is
Device composition	Service disconnect (factory installed)	
Service disconnect rated current	200 A	— squs
Branch circuit breaker rated current	200 A	S. C.
Service feed location	UG	
Bypass type	Class 320 lever bypass	— i

Ordering and shipping details

Category	00022 - QO METER MAINS
Discount Schedule	DE3A
GTIN	00785901468455
Nbr. of units in pkg.	1

Offer Sustainability		
Country of origin	IVIA	
Country of origin	MX	
Returnability	Υ	
Package weight(Lbs)	115	

Off	er	Su	ısta	ıin	ab	ili	tν
0	0.	-			un		·y

Sustainable offer status	Not Green Premium product
RoHS (date code: YYWW)	Will be compliant on 3Q2014
	Will be compliant on 3Q2014
REACh	Reference not containing SVHC above the threshold
	Reference not containing SVHC above the threshold
	Reference not containing SVHC above the threshold

Contractual warranty

Warranty period	18 months