

# RL00402

## REACTOR DRIVE LINE 3PH 1Hp 208/230V Open

Product availability : Stock - Normally stocked in distribution facility



### Complementary

|                       |   |
|-----------------------|---|
| [In] rated current    | 4 A   |
| AWG gauge             | AWG 22...AWG 14   |
| Depth                 | 4.1 in  |
| Electrical connection | Screw clamp terminal  |
| Height                | 2.8 in  |
| Permissible voltage   | <= 600 V AC   |
| Product weight        | 4 lb(US)  |
| Protection type       | Harmonic distortion<br>Overvoltage protection<br>Current protection |
| Width                 | 4.4 in  |

### Environment

|                           |   |
|---------------------------|---|
| NEMA degree of protection | No enclosure rating (open device)           |
| Product certifications    | CSA LR29753<br>UL listed file E180243<br>CE |

### Ordering and shipping details

|                       |  |
|-----------------------|--|
| Category              | 22062 - LINE REACTORS/FILTERS (RL,KLC) |
| Discount Schedule     | CP4C                                   |
| GTIN                  | 00785901884378                         |
| Nbr. of units in pkg. | 1                                      |
| Package weight(Lbs)   | 4                                      |
| Returnability         | Y                                      |
| Country of origin     | US                                     |

Contractual warranty

---

|                 |           |
|-----------------|-----------|
| Warranty period | 18 months |
|-----------------|-----------|

---