

# RPZF1

socket RPZ - mixed contact - 16 A - 250 V - screw clamp

Product availability : Stock - Normally stocked in distribution facility

Price\* : 4.30 USD



## Main

|                              |                           |
|------------------------------|---------------------------|
| Range of product             | Zelio Relay               |
| Product or component type    | Socket                    |
| Contact terminal arrangement | Mixed                     |
| Product compatibility        | Plug-in relay RPM (1 C/O) |
| Device short name            | RPZ                       |

## Complementary

|   |  |
|---|--|
| [Ith] conventional free air thermal current | 15 A   |
| System Voltage                              | 250 V  |
| Tightening torque                           | <= 8.85 lbf.in (1 N.m) (M3.5 screw(s))<br><= 7.08 lbf.in (0.8 N.m) (M3 screw(s)) |
| Fixing mode                                 | By screw mounting on panel<br>Clip-on mounting on 35 mm symmetrical DIN rail     |
| Product weight                              | 0.07 lb(US) (0.031 kg)   |

## Environment

|                         |   |
|-------------------------|---|
| Connections - terminals | Contact terminal - screw clamp terminals, 2 wires solid cable without cable end 0.5...4 mm <sup>2</sup> / AWG 20...AWG 12<br>Contact terminal - screw clamp terminals, 1 wire solid cable without cable end 0.5...4 mm <sup>2</sup> / AWG 20...AWG 12<br>Contact terminal - screw clamp terminals, 2 wires flexible cable with cable end 0.5...2.5 mm <sup>2</sup> / AWG 20...AWG 14<br>Contact terminal - screw clamp terminals, 1 wire flexible cable with cable end 0.5...2.5 mm <sup>2</sup> / AWG 20...AWG 14<br>Coil terminal - screw clamp terminals, 2 wires solid cable without cable end 0.5...2.5 mm <sup>2</sup> / AWG 20...AWG 14<br>Coil terminal - screw clamp terminals, 1 wire solid cable without cable end 0.5...2.5 mm <sup>2</sup> / AWG 20...AWG 14 |
|-------------------------|---|

Coil terminal - screw clamp terminals, 2 wires flexible cable with cable end 0.5...1.5 mm<sup>2</sup> / AWG 20...AWG 16  
 Coil terminal - screw clamp terminals, 1 wire flexible cable with cable end 0.5...1.5 mm<sup>2</sup> / AWG 20...AWG 16

|                                       |   |
|---------------------------------------|---|
| Standards                             | IEC 61984<br>UL 508<br>CSA C22.2 No 14                |
| Product certifications                | CE<br>CSA<br>RoHS<br>UL<br>REACH<br>EAC<br>China RoHS |
| Ambient air temperature for storage   | -40...185 °F (-40...85 °C)                            |
| Ambient air temperature for operation | -40...131 °F (-40...55 °C)                            |
| IP degree of protection               | IP20 conforming to EN/IEC 60529                       |
| Dielectric strength                   | 2500 V  |

### Ordering and shipping details

|                       |  |
|-----------------------|--|
| Category              | 21128 - ZELIO ICE CUBE RELAY ACCESSORIES |
| Discount Schedule     | CP2                                      |
| GTIN                  | 00785901573265                           |
| Nbr. of units in pkg. | 10                                       |
| Package weight(Lbs)   | 8.999999999999997E-2                     |
| Returnability         | Y  |
| Country of origin     | CN                                       |

### Contractual warranty

|                 |           |
|-----------------|-----------|
| Warranty period | 18 months |
|-----------------|-----------|