
Product data sheet Characteristics

RSZE1S48M

socket RSZ - separate contact - < 250 V AC - screw connector

Product availability: Stock - Normally stocked in distribution facility

Price*: 5.30 USD



Main

Man		<u> </u>
Range of product	Zelio Relay	7
Product or component type	Socket	
Contact terminal arrangement	Separate	*
Product compatibility	Plug-in relay RSB (1 C/O) Plug-in relay RSB (2 C/O)	# # # # # # # # # # # # # # # # # # #
Shape of pin	Flat	
Device short name	RSZ	
Sale per indivisible quantity	10	

Complementary

[lth] conventional free air thermal current	10 A	
System Voltage	< 250 V AC	
Tightening torque	<= 7.08 lbf.in (0.8 N.m) (M3 screw(s))	
Fixing mode	By screw mounting on panel Clip-on mounting on 35 mm symmetrical DIN rail	
Marking	CE	
Width	0.61 in (15.5 mm)	
Product weight	0.11 lb(US) (0.05 kg)	7

Environment

Connections - terminals	Screw connectors, flexible cable with cable end 1 x 0.251 x 2.5 mm² / AWG 22AWG 14 Screw connectors, flexible cable with cable end 2 x 0.252 x 1 mm² / AWG 22AWG 17 Screw connectors, solid cable without cable end 1 x 0.51 x 2.5 mm² / AWG 20AWG 14 Screw connectors, solid cable without cable end 2 x 0.52 x 1.5 mm² / AWG 20AWG 16	:
Standards	IEC 61984	i
Product certifications	CSA	

UL

Ambient air temperature for storage	-40185 °F (-4085 °C)
Ambient air temperature for operation	-13185 °F (-2585 °C)
IP degree of protection	IP20 conforming to EN/IEC 60529
Dielectric strength	2500 V

Ordering and shipping details

21128 - ZELIO ICE CUBE RELAY ACCESSORIES
CP2
00785901618195
10
8.000000000000002E-2
Υ
CN

Contractual warranty

Warranty period 18 months
