

Product availability : Stock - Normally stocked in distribution facility



Price* : 89.00 USD



Main

Range of product	Modicon TM3
Product or component type	Remote receiver module
Range compatibility	Modicon M221 Modicon M241 Modicon M251
[Us] rated supply voltage	24 V DC external supply (tolerance: - 15...20 %)

Complementary

Number of I/O expansion module	7
Power supply output current	560 mA at 5 V for expansion bus 560 mA at 24 V for expansion bus
Current consumption	40 mA at 24 V DC via bus connector
Power dissipation in W	<= 1 W
Cable length	0.5...5 m extension cable with 2 RJ45 conductor between receiver and transmitter
Local signalling	1 LED green link status 1 LED green power supply
Electrical connection	RJ45 connector for connecting the bus transmitter Removable screw terminal block with 3 terminal(s) for connecting the 24 V DC power supply
Marking	CE
Resistance to electrostatic discharge	8 kV in air - EN/IEC 61000-4-2 6 kV on contact - EN/IEC 61000-4-2
Resistance to electromagnetic fields	9.14 V/yd (10 V/m) (80 MHz...1 GHz) - EN/IEC 61000-4-3 2.74 V/yd (3 V/m) (1.4 GHz...2 GHz) - EN/IEC 61000-4-3 0.91 V/yd (1 V/m) (2...2.7 GHz) - EN/IEC 61000-4-3
Resistance to conducted disturbances, induced by radio frequency fields	10 Vrms (0.15...80 MHz) - EN/IEC 61000-4-6 3 Vrms (spot frequency (2, 3, 4, 6.2, 8.2, 12.6, 16.5, 18.8, 22, 25 MHz)) - Marine specification (LR, ABS, DNV, GL)
Electromagnetic emission	Radiated emissions - EN/IEC 55011 class A 10 m, 230 MHz...1 GHz: 47 dBµV/m QP Radiated emissions - EN/IEC 55011 class A 10 m, 30...230 MHz: 40 dBµV/m QP
Mounting support	Top hat type TH35-15 rail conforming to IEC 60715 Top hat type TH35-7.5 rail conforming to IEC 60715

	Plate or panel with fixing kit
Height	3.54 in (90 mm)
Depth	2.89 in (73.3 mm)
Width	0.93 in (23.65 mm)
Product weight	0.17 lb(US) (0.075 kg)

Environment

Standards	CSA C22.2 No 142 CSA C22.2 No 213 (Class I Division 2 Groups A/B/C/D) IEC 61131-2 UL 1604 (Class I Division 2 Groups A/B/C) UL 508
Product certifications	CSA HazLoc C-Tick GOST Merchant Navy
Ambient air temperature for operation	14...131 °F (-10...55 °C) horizontal installation 14...122 °F (-10...50 °C) vertical installation
Ambient air temperature for storage	-40...158 °F (-40...70 °C)
Relative humidity	5...95 % without condensation
IP degree of protection	IP20 with protective cover in place
Pollution degree	2
Operating altitude	0...6561.68 ft (0...2000 m)
Storage altitude	0...9842.52 ft (0...3000 m)
Vibration resistance	3.5 mm (vibration frequency: 5...8.4 Hz) on DIN rail 3 gn (vibration frequency: 8.4...150 Hz) on DIN rail 3.5 mm (vibration frequency: 5...8.4 Hz) on panel 3 gn (vibration frequency: 8.4...150 Hz) on panel
Shock resistance	15 gn (test wave duration:11 ms)

Ordering and shipping details

Category	22533 - M2XX PLC & ACCESSORIES
Discount Schedule	MSX
GTIN	00785901978312
Nbr. of units in pkg.	1
Package weight(Lbs)	0.37
Returnability	Y
Country of origin	ID

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1408 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold
Product environmental profile	Available
Product end of life instructions	Available