

TVS3HWA10X

HWA Surge Protection Device 120/240V HLD 3PH, 4WIRE, 100kA

Product availability : Stock - Normally stocked in distribution facility



Price* : 3611.00 USD



Main

Device short name	HWA
Provided equipment	Alarm LED
Range of product	SurgeLogic

Complementary

System Voltage	120/240 V AC
AWG gauge	AWG 10 (aluminium/copper)
[Uc] maximum continuous operating voltage	150...270 V
Device mounting	Flush Surface
Local signalling	Status green = normal operation per phase Status red = fault per phase
Mounting location	Bottom of enclosure
Number of poles	2
Phase	3 phases
OverId and short-circuit prot	100 kA
Surge current	<= 100 kA per phase
Wiring configuration	4-wire
Nominal discharge current	20 kA

Environment

NEMA degree of protection	NEMA 4X
Standards	CSA C22.2 No 8 1986 UL 1449 ed. 3 UL 1283 ed. 5

Ordering and shipping details

Category	08466 - SURGE PROTECTION HWA
Discount Schedule	DE1B
GTIN	00785901946434
Nbr. of units in pkg.	1
Package weight(Lbs)	3.8999999999999999
Returnability	N
Country of origin	MX

Offer Sustainability

Sustainable offer status	Not Green Premium product
--------------------------	---------------------------

Contractual warranty

Warranty period	18 months
-----------------	-----------