



Main

Product or component type	Communication card
Range compatibility	Altivar 71 Altivar 71Q Altivar 61Q Altivar 61
Communication port protocol	Ethernet/IP
Connector type	2 RJ45 connectors
Transmission rate	10 Mbps 100 Mbps
Physical interface	IEEE 802.3
Web services	Security Ethernet/IP setup Ethernet/IP scanner setup E-mail Drive parameters Drive monitor Drive recorder Ethernet statistics Message statistics

Complementary

Exchange mode	Half duplex and full duplex
Communication data link	LLC : IEEE 802.2 MAC : IEEE 802.3
Communication network type	ICMP IP conforming to RFC791
Communication transport type	TCP conforming to RFC793 UDP
Web server	Embedded
Communication service	Allen-Bradley drive profile BOOTP CiA 402 profile

	CIP AC Drive (02) profile CIP I/O data DHCP I/O profile
Display type	1 LED Link (Link Status) 1 LED MS (Module Status) 1 LED NS (Network Status) 1 LED TX/RX (Transmit/Receive port 1) 1 LED TX/RX (Transmit/Receive port 2) Graphic display terminal control word received Graphic display terminal number of frames received Graphic display terminal reference received
Product weight	0.66 lb(US) (0.3 kg)

Ordering and shipping details

Category	22135 - ATV61-71 ACCESSORIES
Discount Schedule	CP4C
GTIN	00785901525196
Nbr. of units in pkg.	1
Package weight(Lbs)	0.6600000000000003
Returnability	Y
Country of origin	ID

Contractual warranty

Warranty period	18 months
-----------------	-----------