

Product availability : Stock - Normally stocked in distribution facility



### Main

Product or component type	Controller inside programmable card
Range compatibility	Altivar 61Q Altivar Lift Altivar 71Q Altivar 61 Altivar 71
[Us] rated supply voltage	24 V
Supply circuit type	DC
Analogue input number	2
Analogue input type	AI51, AI52 current analog input: 0...20 mA, impedance: 250 Ohm, resolution: 10 bits
Analogue output number	2
Analogue output type	AO51, AO52 current analog output: 0...20 mA, impedance: 500 Ohm, resolution: 10 bits
Discrete input number	10
Discrete input type	(LI51...LI60) logic inputs, 24 V DC, compatible with level 1 PLC (voltage limits: <= 30 V), impedance: 4.4 kOhm
Discrete input logic	(LI51...LI60) positive state 0 <= 5 V state 1 >= 11 V
Discrete output number	6
Discrete output type	(LO51...LO56) logic output, compatible with level 1 PLC
Discrete output logic	(LO51...LO56) positive
Battery type	Lithium
Application program desc	Compiled program size : 320 kB maximum Data size : 64 kwords maximum Data saved size : 4 kwords Data size accessible by Modbus : 2 kwords
Transmission rate	50 kbps, 125 kbps, 250 kbps, 500 kbps, 1 Mbps

### Complementary

Supply voltage limits	19...30 V
Current consumption	2 A maximum

	200 mA maximum per logic output 80 mA no load
Discrete output voltage	24 V DC, maximum switching voltage: 30 V logic output
Output current limits	0.2 A, logic output
Electrical connection	Terminal, 1.5 mm <sup>2</sup> / AWG 16, 2.21 lbf.in (0.25 N.m)
Battery life	8 yr
Communication port protocol	CANopen
Connector type	9-way male SUB-D connector
Method of access	Master
Number of addresses	1...32
Communication service	2 client SDOs per slave DSP 405 DS 301 V4.02 10 receive and transmit PDOs in total for each slave Emergency, boot-up, sync
Display type	1 LED ERROR (fault) 1 LED RUN (status)
Product weight	0.71 lb(US) (0.32 kg)

### Ordering and shipping details

Category	22135 - ATV61-71 ACCESSORIES
Discount Schedule	CP4C
GTIN	00785901504085
Nbr. of units in pkg.	1
Package weight(Lbs)	0.9200000000000004
Returnability	Y
Country of origin	ID

### Contractual warranty

Warranty period	18 months
-----------------	-----------