Product data sheet Characteristics

XBTN401

small panel with keypad - with matrix screen - G-O-R - 24 V

Product availability: Stock - Normally stocked in distribution facility



Main

Range of product	Magelis XBTN	9
Product or component type	Small panel with keypad	
Display resolution	122 x 32 pixels	±
Software type	Configuration software)c
Software designation	Vijeo Designer Lite	<u> </u>
Operating system	Magelis	<u> </u>

Complementary

Display type	Extra-bright matrix backlit LCD
Display colour	Orange Green Red
Character font	ASCII Cyrillic Chinese (simplified Chinese) Greek Katakana
[Us] rated supply voltage	24 V DC
Supply	External source
Supply voltage limits	1830 V
Residual ripple	1200 mV
Power consumption in W	<= 5 W
Number of key	8
Number of fixed keys	4
Number of customisable keys	4
Local signalling	6 LEDs
Number of pages	200 application pages 256 alarm pages
Memory type	Flash

Memory capacity	512 kB
Integrated connection type	Power supply: removable screw terminal block Printer port: female mini DIN Serial link: female SUB-D 25, asynchronous transmission mode (RS232C/RS485), multidrop topology
Realtime clock	Access to the PLC real-time clock
Product mounting	Flush mounting
Fixing mode	By 2 spring clips
Display material	Polyester
Front material	PPT
Keypad material	Polyester
Marking	CE
Width	5.2 in (132 mm)
Height	2.91 in (74 mm)
Depth	1.69 in (43 mm)
Cut-out dimensions	119.4 (+/- 0.5) x 63 (+/- 0.4) mm
Product weight	0.84 lb(US) (0.38 kg)

Environment

Messages display capacity	4 lines of 20 characters maximum
	1 line of 5 characters minimum
Downloadable protocols	Third party protocols
	Uni-TE
	Modbus
Standards	IEC 60068-2-27
	IEC 61131-2
	IEC 60068-2-6
	UL 508
	CSA C22.2 No 14
Product certifications	CSA Class 1 Division 2
	UL Class 1 Division 2
	ATEX zone 2/22
	UL 1604
Ambient air temperature for operation	32131 °F (055 °C)
Ambient air temperature for storage	-4140 °F (-2060 °C)
Relative humidity	085 % without condensation
IP degree of protection	IP20 (rear panel) conforming to IEC 60529
	IP65 (front panel) conforming to IEC 60529
NEMA degree of protection	NEMA 4X front panel (outdoor use)
Shock resistance	15 gn 11 ms
Vibration resistance	+/- 3.5 mm (f = 28.45 Hz)
	1 gn (f = 8.45150 Hz)

Ordering and shipping details

Category	22570 - MAGELIS TEXT DISPLAYS & ACCESS
Discount Schedule	MC2
GTIN	00785901673392
Nbr. of units in pkg.	1
Package weight(Lbs)	0.940000000000006
Returnability	Υ
Country of origin	CN

Contractual warranty

Warranty period	18 months