Product data sheet Characteristics

ZB4BPA3

green flush pushbutton head Ø22 spring return unmarked

Product availability: Stock - Normally stocked in distribution facility



Main

Range of product	Harmony XB4	
Product or component type	Head for non-illuminated push-button	
Device short name	ZB4	
Product compatibility	Not compatible with legend holder	
Bezel material	Chromium plated metal	
Mounting diameter	0.87 in (22 mm)	
Sale per indivisible quantity	1	
Shape of signaling unit head	Round	
Type of operator	Spring return	:
Operator profile	Green flush unmarked	
Operator additional information	Clear boot	

Complementary

CAD overall width	1.18 in (30 mm)	
CAD overall height	1.18 in (30 mm)	
CAD overall depth	1.46 in (37 mm)	
Mechanical durability	10000000 cycles	-

Environment

Protective treatment	TH
Ambient air temperature for storage	-40158 °F (-4070 °C)
Ambient air temperature for operation	-40158 °F (-4070 °C)
Overvoltage category	Class I conforming to IEC 60536
IP degree of protection	IP67 IP66 conforming to IEC 60529
NEMA degree of protection	NEMA 13 NEMA 4X

IK degree of protection	IK06 conforming to IEC 50102	
Standards	JIS C 4520 EN/IEC 60947-1 EN/IEC 60947-5-4 CSA C22.2 No 14 EN/IEC 60947-5-1 UL 508 EN/IEC 60947-5-5	
Product certifications	UL listed CSA BV LROS (Lloyds register of shipping) RINA DNV GL	
Vibration resistance	5 gn (f = 2500 Hz) conforming to IEC 60068-2-6	
Shock resistance	30 gn (duration = 18 ms) half sine wave acceleration conforming to IEC 60068-2-27 50 gn (duration = 11 ms) half sine wave acceleration conforming to IEC 60068-2-27	

Ordering and shipping details

Category	22468 - PUSHBUTTONS,22MM(METAL) NEW		
Discount Schedule	CS2		
GTIN	00785901121114		
Nbr. of units in pkg.	1		
Package weight(Lbs)	7.00000000000007E-2		
Returnability	Υ		
Country of origin	FR		

Contractual warranty

Warranty period	18 months	
· .		