

# ZB4BV01

white pilot light head Ø22 with plain lens for BA9s bulb

Product availability : Stock - Normally stocked in distribution facility



## Main

|                                 |                       |
|---------------------------------|-----------------------|
| Range of product                | Harmony XB4           |
| Product or component type       | Head for pilot light  |
| Product compatibility           | BA 9s                 |
| Device short name               | ZB4                   |
| Bezel material                  | Chromium plated metal |
| Mounting diameter               | 0.87 in (22 mm)       |
| Sale per indivisible quantity   | 1                     |
| Shape of signaling unit head    | Round                 |
| Cap/Operator or lens colour     | White                 |
| Operator additional information | With plain lens       |

## Complementary

|                                    |  |
|------------------------------------|--|
| CAD overall width                  | 1.14 in (29 mm)  |
| CAD overall height                 | 1.14 in (29 mm)  |
| CAD overall depth                  | 1.22 in (31 mm)  |
| Product weight                     | 0.06 lb(US) (0.027 kg)   |
| Resistance to high pressure washer | 1015.26 psi (7000000 Pa) at 131 °F (55 °C), distance: 0.1 m                        |
| Electrical composition code        | P3 in front mounting with BA 9s<br>P4 in front mounting with BA 9s and transformer |
| Main group                         | Pilot light  |
| Group of product                   | Lens fitted BA9s   |
| Cap/Operator or lens colour        | White  |
| Compatibility code                 | ZB4  |

## Environment

|                      |    |
|----------------------|----|
| Protective treatment | TH |
|----------------------|----|

|                                       |  |
|---------------------------------------|--|
| Ambient air temperature for storage   | -40...158 °F (-40...70 °C)   |
| Ambient air temperature for operation | -40...131 °F (-40...55 °C)   |
| Electrical shock protection class     | Class I conforming to IEC 60536  |
| Overvoltage category                  | Class I conforming to IEC 60536  |
| IP degree of protection               | IP69<br>IP67<br>IP66 conforming to IEC 60529<br>IP69K  |
| NEMA degree of protection             | NEMA 13<br>NEMA 4X   |
| IK degree of protection               | IK06 conforming to IEC 50102   |
| Standards                             | UL 508<br>CSA C22.2 No 14<br>EN/IEC 60947-5-5<br>JIS C 4520<br>EN/IEC 60947-1<br>EN/IEC 60947-5-4<br>EN/IEC 60947-5-1  |
| Vibration resistance                  | 5 gn (f = 2...500 Hz) conforming to IEC 60068-2-6  |
| Shock resistance                      | 30 gn (duration = 18 ms) half sine wave acceleration conforming to IEC 60068-2-27<br>50 gn (duration = 11 ms) half sine wave acceleration conforming to IEC 60068-2-27 |

### Ordering and shipping details

|                       |                                     |
|-----------------------|-------------------------------------|
| Category              | 22468 - PUSHBUTTONS,22MM(METAL) NEW |
| Discount Schedule     | CS2                                 |
| GTIN                  | 00785901371526                      |
| Nbr. of units in pkg. | 1                                   |
| Package weight(Lbs)   | 4.0000000000000001E-2               |
| Returnability         | Y                                   |
| Country of origin     | FR                                  |

### Contractual warranty

|                 |           |
|-----------------|-----------|
| Warranty period | 18 months |
|-----------------|-----------|