

Representative

Catalog Number: FPT4-4P-4C-TBLK
Product ID: 7TAA003440R0010
UPC Number: 78599105673

Status: Active

Poke-Through Base Unit, 4 Inch Drill Size, 19 Inch Length, Hub Size 1/2 Inch and 1 Inch, Galvanized Steel, with 4 20A Power Receptacles and 4 Cat-5e Data Jacks with Device Plates, Base with Black Cover

- Four modular configurations for power receptacles and communications jacks mounted flush with the floor.
- Full access to communications compartment through the cover without exposing power compartments even after it is installed in the floor.
- Threaded conduit hubs enable all communications cabling to be enclosed in a single conduit
- Accommodates fiber optic and audio/video connectors
- · Pre-wired power receptacles

North American Specifications (UNSPSC)		
UNSPSC	39121328 Fire rated poke through box	
IGCC	4482 Fire rated poke through box	
Brand Name	Steel City	
Туре	Poke Through Systems	
Special Features	Four modular configurations for power receptacles	
	and communications jacks mounted flush with the	
	floor.	
Application	For above-grade, fire rated concrete floors.	
Standard	UL e2969	
Material	Die Cast Zinc/Galvanized Steel	
Color	Black	
Knockouts	10	

European Specifications (ETIM)		
ETIM	EC000024 Installation box for underfloor-installation	
Cover model	Round	
Suitable for wet cleaning	N	
Suitable for hollow floor	Υ	
Material	Other	
With opening carpeting	N	
Colour	Other	
Length external dimension	482.6mm	

Packaging	
Outer Quantity	1
Outer Dimensions (inches)	21.38x8.13x5.5
Weight Uom	8.49 lbs. Each

<b>Documents / Support Tools</b>	
Technical Drawing / Data Sheet	WSD-000579
Technical Drawing / Data Sheet Canada	Available on Website
Support/Tools	Available on Website

Header	
3D Model	Available on Website

For further technical assistance, please contact us...



ABB Installation Products - USA 860 Ridge Lake Blvd. Memphis, TN 38120 www.tnb.com ABB Installation Products Technical Support MS 3B-50 860 Ridge Lake Blvd. Memphis, TN 38120 Hours: 7AM - 6PM CDT Monday-Friday Phone: (888) 862-3289 Fax: (901) 252-1321 Email:techsupport@tnb.com