homas&Betts



Actual

Catalog Number: Product ID: **UPC Number:** Status:

XD010-TB 7TAD013840R0000 78620989420 Active

4 Inch XD Cast Iron Expansion/Deflection Coupling with Electro Zinc Plating

- · Suitable for use indoors, outdoors, direct buried or embedded in concrete.
- Watertight, flexible neoprene outer jacket, zinc-plated and acrylic-painted hubs and ٠ stainless steel tamper proof straps ensure superior corrosion resistance, ideal for use in harsh environments.
- Copper ground mounting plates and internal grounding bonding jumper both entirely enclosed to safeguard against theft.
- · Includes an Erickson® type conduit union for faster, easier installation to reduce labor costs.
- · Durable stainless steel inner sleeve provides a constant, smooth inner diameter in any position to ease wire pulling and protect wire insulation from damage.
- · Applications in which conduit runs are subject to movement due to external forces or temperature changes.
- Watertight-NEMA 4

• UL Listed to UL 514B and CSA Certified to C22.2 No. 18.3 Suitable for wet locations hub sizes 1 inch - 2 1/2 inch

North American Specifications (UNSPSC)		
UNSPSC	39131707 Electrical conduit coupling	
IGCC	5548 Electrical conduit coupling	

IGCC	5548 Electrical conduit coupling
Brand Name	T&B
Туре	XD Expansion/Deflection Couplings
Special Features	Accommodates Axial Expansion/contraction Up to
	3/4 Inch, Parallel Deflection Up to 3/4 Inch and An-
	gular Misalignment Up to 30 Degree.
Application	Bridges, Tunnels, Inter-Building Walkways, Docks
	and Piers and Wastewater and Water Treatment
	Facilities
Standard	CSA, UL E23018
Trade Size	4 Inch
Material	Ductile Cast Iron

European Specifications (ETIM)

· ·	
ETIM	EC000939 Coupler for installation tubes
Material	Metal
Material quality	Other
Surface protection	Galvanic/electrolytic zinc plated
Model	Thread
Two piece	Ν
With inspection opening and cover	Ν

Packaging

Outer Quantity	1		
Outer Dimensions (inches)	165x10.75x10.75		
Weight Uom	36.15 lbs. Each		

Documents / Support Tools

Technical Drawing / Data Sheet	WSD-000096
Technical Drawing / Data Sheet Canada	Available on Website
Instruction Sheet	TA04233-TB2





Header

3D Model

Available on Website

For further technical assistance, please contact us...

ABB Installation Products Technical Support MS 3B-50 860 Ridge Lake Blvd. Memphis, TN 38120 Hours: 7AM - 6PM CDT Monday-Friday Phone: (888) 862-3289 Fax: (901) 252-1321 Email:techsupport@tnb.com

ABB Installation Products - USA 860 Ridge Lake Blvd. Memphis, TN 38120 www.tnb.com